


BENEFITS

- Microthin surface layer
- Perfect for small characters and detailed logos
- Gravoply™ 2 Gloss has an extra durable, scratch resistant, glossy cap



APPLICATIONS

Badges, identification plates, interior signage

SPECIFICATIONS

Finish	Matt
Composition	ABS
Engraving depth	0.1 mm (.004")
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	-
Shear	■
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	■
Flexible	■
Break resistant	■
UV resistant	-
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

You can mix any surface and core colours on demand. Double-sided products are also available.

For custom colours, see Custom materials on demand p. 10.

surface / core colour	2-ply					
	0.5 mm (.020")	0.8 mm (1/32")	1.5 mm (1/16")	2.4 mm (3/32")	1.5 mm (1/16")	3.2 mm (1/8")
white / red	21857	21928	23981			
white / burgundy	21874	21874				
white / azure blue	21841	21908	21973			
white / black	53218	21850	21919	21982	23977	22010
almond / burgundy		29709				
almond / black	21855	21926				
yellow / red	21845	21913				
yellow / azure blue	21828	21896				
yellow / black	21863	21936	21995	23982	22013	
dark yellow / black		21925				
orange / white		52205				
red / white	53219	21851	21921	21983	23978	22016
red / yellow		21910				
burgundy / white		21932				
purple / white	67007					
apple green / white	21838	21905				
pine green / white	21865	21938	21997	23983		
pine green / yellow		21916				
sky blue / white	21861	21934				
sky blue / black	21827	21895				
blue / white	53220	21852	21923	21984	23979	22012
blue / yellow		21911				
air force blue / white		21907				
brown / white	21858	21930				
chocolate brown / white		21876				
grey / white	21856	21927		23980		
grey / black		21915				
black / white	53217	21849	21917	21981	23976	22009
black / yellow	21866	21940			22009	29732

* Gravoply™ 2 products have a laserable foil cap but engraving colour results can vary according to the reference. Vector cutting is not recommended.



The dimensions indicated represent our minimal commitment. Printed colours for indication only. Cannot serve as a substitute for real material sample.

