

BENEFITS

- This unique material offers 3 layers of colour for surface engraving
- The colour revealed varies according to the depth of engraving
- Only one tool required to achieve two different colours
- Ideal for safety signs

APPLICATIONS

Signage, plates with logos, badges

SPECIFICATIONS

Finish	Matt
Composition	ABS
Engraving depth	0.1 mm (.004") - 0.3 mm (.012")
Full sheet	1220 mm x 600 mm (48" x 24")
Half sheet	610 mm x 600 mm (24" x 24")
Quarter sheet	600 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	-
Shear	■
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	■
Flexible	■
Break resistant	■
UV resistant	-
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

Unique on the engraving market, it is the only 3-colour material that does not require colouring.

Other colour combinations available on demand. Contact us for more information.

For custom colours, see Custom materials on demand p.10.



Rotary



UV Print



Indoor



Surface

surface / core colour / core colour	3-ply	1.6 mm (1/16")
white / red / black	23957	23957
yellow / white / black	23949	23949
yellow / red / black	23954	23954
red / white / black	23955	23955
apple green / white / black	23953	23953
blue / white / black	23956	23956
blue / red / white	23952	23952
brushed aluminium / black / white	23951	23951
radiant gold / black / white	23950	23950
black / red / white	23948	23948

GRAVOGRAPH 

Printed colours for indication only. Cannot serve as a substitute for real material sample.

