

BENEFITS

- For indoor and outdoor use
- UV stable
- Subsurface engraving

APPLICATIONS

Indoor and outdoor signage,  
professional plates, directories

SPECIFICATIONS

Finish	Matt
Composition	DR Acrylic
Engraving depth	0.3 mm (.012")
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	-
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	■
Flexible	-
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

UV stability for outdoor signage.

You can use Gravograph recommended paint to colour any Gravoglas™ 2-Plex™ subsurface engraving. See p.55.

For custom colours, see Custom materials on demand p.10.



Subsurface engraving  
Matt

surface / backing colour	2-ply	
	1.6 mm (1/16")	3.2 mm (1/8")
clear / clear	17941	18082
clear / white	17947	18086
clear / eggshell	33982	
clear / almond	17958	33977
clear / cream	29658	
clear / yellow	17956	
clear / red	17950	18088
clear / bordeaux	29659	
clear / burgundy	17976	
clear / apple green	17973	
clear / green	29662	34381
clear / azure blue	17953	33962
clear / american blue	29663	
clear / royal blue	29665	
clear / metallic blue	29666	

surface / backing colour	2-ply	
	1.6 mm (1/16")	3.2 mm (1/8")
clear / cocoa	29660	
clear / taupe	29661	
clear / chocolate brown	17970	34363
clear / silver grey	17961	34406
clear / slate	29667	
clear / silver	29669	
clear / gold	29670	
clear / black	17944	18084



The dimensions indicated represent our minimal commitment. Printed colours for indication only. Cannot serve as a substitute for real material sample.

