



Subsurface engraving
Glossy

surface / backing colour	2-ply	
	1.6 mm (1/16")	3.2 mm (1/8")
clear / clear	29655	29657
clear / white	17988	18021
clear / almond	18015	18101
clear / yellow	18003	18036
clear / red	17997	18030
clear / air force blue	17938	18018
clear / azure blue	18000	18033
clear / silver grey	29656	
clear / silver	17985	18093
clear / gold	17982	18091
clear / black	17991	18024
		18104

BENEFITS

- For indoor and outdoor use
- UV stable
- Subsurface engraving

APPLICATIONS

Indoor and outdoor signage, professional plates, directories

SPECIFICATIONS

Finish	Glossy
Composition	DR Acrylic
Engraving depth	0.3 mm (.012")
Full sheet	1 220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	-
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	■
Flexible	-
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

UV stability for outdoor signage.
You can use Gravograph recommended paint to colour any Gravoglas™ 2-Plex™ subsurface engraving. See p.55.
For custom colours, see Custom materials on demand p.10.

The dimensions indicated represent our minimal commitment.
Printed colours for indication only. Cannot serve as a substitute for real material sample.

