



	0.8 mm (1/32")	1.6 mm (1/16")	3.2 mm (1/8")
clear	29918	29935	72083
white	29919	29936	31237
almond	29921	29938	32295
red	29922	29939	31700
burgundy	29923	29940	31738
pine green	29927	29944	31837
teal	29933	29903	
azure blue	29928	29945	31406
silver	29931		
silver grey	29929	29946	32187
slate	29930	29947	32277
chocolate brown	29926	29943	31648
gold	29932		
black	29920	29937	31257

BENEFITS

- Interior and exterior use
- Profile available with or without adhesive backing
- Cut with laser or rotary machines

APPLICATIONS

DDA & ADA compliant, tactile signage

SPECIFICATIONS

Finish	Matt
Composition	Impact modified acrylic
Engraving depth	-
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	-
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	■
Flexible	■
Break resistant	■
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

The Gravotac™ process :



Adhere 0.8 mm (1/32") profile material to 1.6 mm (1/16") or 3.2 mm (1/8") substrate. Engrave using outline font. Peel excess profile material off substrate.

The dimensions indicated represent our minimal commitment. Printed colours for indication only. Cannot serve as a substitute for real material sample.



TECH TIPS

The ideal product for Braille and tactile signs cut with your laser machine. UV stable.

