

FLEX FRAMES *Tamper Resistant Sign Frames*

Attractive, functional and flexible, FLEX is a tamper resistant sign frame option that can be utilized for virtually any interior signage application. Square side rails with finished ends use a mix of our wall brackets that slide into the rails and are secured with a setscrew combination offering a wide range of signage options while maintaining ease of maintenance and changeability. FLEX can be mounted using magnets inside of our other frame systems* to make simple personnel signs or directories. Available in 5 anodized colors: **SATIN SILVER, POLISHED SILVER, MATTE BLACK, POLISHED YELLOW GOLD AND POLISHED ROSE GOLD.**



HUMAN RESOURCES	
CAMERON MEYER	C122
MICAELA SMITH-LAMB	C123
JESSE PELLEGRINO	C124
KYLE HANSON	C125
AUSTIN TAYLOR	C126
DAVE GRIFFITTS	C127

PN 301

CLIFFORD STENDER, LMFT
KELLY WALLACE, LMFT
LIZ THOMPSON, MA, Ph.D.

<i>Design Team</i>
<i>Kristin Meyer, P.E.</i>
<i>Ashley Finkbiner, P.E.</i>
<i>Richard Jacobson, P.E.</i>



Technical Information

- Square Rail: 3/16" face width and 1/2" outside depth
- Designed to accommodate 1/16" material
- Uses 3/16 ABS backer
- Mounting holes available upon request
- Max rail length = 39"

Installation:

- FLEX can be mounted using magnets inside of our other frame systems* to make simple personnel signs or directories. *Please call for details.
- Frames are designed for mounting with double-sided tape, silicone adhesives or mounting holes. Holes are provided by request only at no additional charge.

Applications:

- Room Identification
- Directional signage/directories
- Personal ID signs
- Departmental ID signs
- A solution for banks, financial institutions, call centers, office facilities, hospitals, schools, colleges and libraries

- See pages 7 & 21 for multiple channel sizes
- Fax or email drawing for directory pricing
- Order using inside dimensions
- Custom made are not returnable

This line is manufactured with a 3/16" ABS backing and comes as a flush wall mount. Screw holes available by request at no charge. Magnetic metal backing can be requested for a nominal charge.

***USES A 5/64" ALLEN WRENCH - NOT INCLUDED**