

BENEFITS

- UV stable
- Excellent for interior and exterior signage
- A wide range of colours
- Matt finish
- Microthin surface layer for detailed engraving
- Reduce inventory with one material for rotary, laser, indoor and outdoor needs

APPLICATIONS

Architectural signage, industrial signage, labelling, legend plates...

SPECIFICATIONS

Finish	Matt
Composition	Acrylic
Engraving depth	0.1 mm (.004")
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	■
Saw	-
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	-
Flexible	■
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

The most versatile plastic material: indoor, outdoor, laser and rotary engraving and cutting. One product, one stock, many applications.

You can mix any surface and any core colours on demand.

For custom colours, see Custom materials on demand p.10.



Flexibility and performance for indoor and outdoor applications

surface / core colour	2-ply		
	0.8 mm (1/32")	1.3 mm (.050")	1.6 mm (1/16")
white / red	51047	51006	70005
white / blue	51057	51011	80763
white / black	51017	49971	69991
almond / black	51022	49978	80764
yellow / red	51048	51007	70006
yellow / blue	51058	51012	80765
yellow / black	51018	49973	69992
dark yellow / black	51019	49977	80766
orange / white	51035	51005	80767
orange / black	51020	51001	80768
red / white	51034	49988	69995
red / yellow	51055	51009	80769
burgundy / white	51043	49997	70004
burgundy / gold	51062	51016	80770
purple / white	67005*	67006*	80771*

\*Subject to premature colorfading



The dimensions indicated represent our minimal commitment. Printed colours for indication only. Cannot serve as a substitute for real material sample.

