



surface / backing colour	2-ply	
	1.5 mm (1/16")	3.0 mm (1/8")
clear / white	18141*	18193
clear / light grey	18177*	18264
clear / golden yellow	18130*	18264
clear / yellow		18217
clear / red	18201	18267
clear / burgundy	18232	18287
clear / purple	18132*	
clear / moss green	18136*	
clear / garden green	18229	18285
clear / green		18282
clear / light blue	18179*	
clear / sky blue	18214	18273
clear / blue	18207	18270
clear / brown	18134*	
clear / silver	18171	18244
		18293

surface / backing colour	2-ply	
	1.5 mm (1/16")	3.0 mm (1/8")
clear / gold	18168	18295
clear / old gold	18174	18252
clear / black	18138*	18183
		18261

BENEFITS

- Laser engraving and cutting
- Excellent UV resistance
- A fine silk-screened layer
- Resistant to chemical agents
- Subsurface engraving: produce multi-colour signage with paint fill
- Easy to keep surface clean
- Interior and exterior use

APPLICATIONS

Interior and exterior signage, professional name plates

SPECIFICATIONS

Finish	Glossy
Composition	Acrylic
Engraving depth	0.2 mm (.008")
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	-
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	■
Flexible	-
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

Excellent material for both rotary and laser engraving.

You can use GravoGraph recommended paint to colour any GravoGlas™ 1 subsurface engraving. See p.55.

For custom colours, see Custom materials on demand p.10.

* Conventional colours for the identification of pipes in the industrial sector (AFNOR NF X. 08-002 and INRS ED 88 norms).

Printed colours for indication only. Cannot serve as a substitute for real material sample.

GRAVOGRAPH

