

BENEFITS

- Laser engraving and cutting
- Glossy or frosted finish
- Excellent for clear signage
- Laser and rotary engravable
- Interior and exterior use



APPLICATIONS

Interior and exterior signage applications

SPECIFICATIONS

Finish	Glossy
Composition	Acrylic
Engraving depth	0.25 mm (0.010")
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	0.5 mm (0.020")
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	-
Scratch resistant	■
Flexible	-
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (180°F)

TECH TIPS

Acrylic sheets can be engraved, paint filled, or used for cutouts. Another common use is to simply add thickness to an engraved sheet of metal or plastic. The added thickness has a strong presence on the wall - especially helpful if the sign is not framed.

white	58820	3.2 mm (.125")
	58821	6.4 mm (.250")
opaque black	34096	3.2 mm (.125")
	34098	6.4 mm (.250")
clear	33971	3.2 mm (.125")
	33972	6.4 mm (.250")

Sold in North America Only



Printed colors for indication only. Cannot serve as a substitute for real material sample. The dimensions indicated represent our minimal commitment.

