


BENEFITS

- For indoor and outdoor use
- UV stable
- Subsurface engraving



APPLICATIONS

Indoor and outdoor signage, professional plates, directories

SPECIFICATIONS

Finish	Matte
Composition	DR Acrylic
Engraving depth	0.3 mm (.012")
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	-
Saw	■
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	■
Flexible	-
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

TECH TIPS

UV stability for outdoor signage.

You can use Gravograph recommended paint to color any Gravoglas™ 2-Plex™ subsurface engraving. See p.67.

For custom colors, see Custom materials on demand p.10.

Subsurface engraving Matte

surface / backing color	2-ply		surface / backing color	2-ply	
	1.6 mm (1/16")	3.2 mm (1/8")		1.6 mm (1/16")	3.2 mm (1/8")
clear / clear	17941	18082	clear / cocoa	29660	29660
clear / white	17947	18086	clear / taupe	29661	29661
clear / eggshell	33982		clear / chocolate brown	17970	34363
clear / almond	17958	33977	clear / silver grey	17961	34406
clear / cream	29658		clear / slate	29667	29667
clear / yellow	17956		clear / silver	29669	29669
clear / red	17950	18088	clear / gold	29670	29670
clear / bordeaux	29659		clear / black	17944	18084
clear / burgundy	17976	18090*			
clear / apple green	17973				
clear / green	29662	34381			
clear / azure blue	17953	33962			
clear / american blue	29663				
clear / royal blue	29665				
clear / metallic blue	29666				

\* Sold in North America Only



Printed colors for indication only. Cannot serve as a substitute for real material sample. The dimensions indicated represent our minimal commitment.

