



Flexibility and performance for indoor and outdoor applications

## Matte

surface / core color	2-ply	0.5 mm (.020")	0.8 mm (1/32")	1.3 mm (.050")	1.6 mm (1/16")	0.8 mm (1/32")
apple green / white		51042	51039	49995	70003	
pine green / white		51039	49995	70002		
sky blue / white		51037	49990	69997		
sky blue / black		51021	49979	69993		
blue / white		51036	49989	69996		
blue / yellow		51056	51010	80772		
blue / gold	72305**					
air force blue / white		51038	49991	69998		
air force blue / gold		51061	51015	80773		
brown / white		51044	49993	70000		
grey / white		51046*	49992*	69999*		
grey / black		51028*	49974*	80774*		
black / white		51033	49987	69994		
black / white / red		51049	51008	80775		71713**
black / yellow		51060	51014	80776		
black / gold						

\*Subject to premature colorfading  
\*\* Sold in North America Only

## Double-sided

## Woodgrains\*\*

surface / core color



\*\* Sold in North America Only

## NEW Reverse\*\*\*

surface / backing color

surface / backing color	2-ply	1.6 mm (1/16")
clear / clear	82369	
clear / white	82170	
clear / red	82171	
clear / blue	82172	
clear / silver	82173	
clear / gold	82174	
clear / black	82175	

Call 1.800.843.7637 to order or visit [www.gravostoreUSA.com](http://www.gravostoreUSA.com)  
Printed colors for indication only. Cannot serve as a substitute for real material sample.  
The dimensions indicated represent our minimal commitment.



## BENEFITS

- UV stable
- Excellent for interior and exterior signage
- A wide range of colors
- Matte finish
- Microthin surface layer for detailed engraving
- Reduce inventory with one material for rotary, laser, indoor and outdoor needs

## APPLICATIONS

Architectural signage, industrial signage, labelling, legend plates...

## SPECIFICATIONS

Finish	Matte
Composition	Acrylic
Engraving depth	0.1 mm (.004")
Full sheet	1220 mm x 610 mm (48" x 24")
Half sheet	610 mm x 610 mm (24" x 24")
Quarter sheet	610 mm x 305 mm (24" x 12")
Other size	-

## CAPABILITIES

Interior	■
Exterior	■
Shear	■
Saw	-
Silk screen	■
Hot stamp	■
Heat bending	■
Scratch resistant	-
Flexible	■
Break resistant	-
UV resistant	■
Min. temp.	-40°C (-40°F)
Max. temp.	80°C (176°F)

## TECH TIPS

The most versatile plastic material: indoor, outdoor, laser and rotary engraving and cutting. One product, one stock, many applications.

You can mix any surface and any core colors on demand.

For custom colors, see Custom materials on demand p.10.

