


BENEFITS

- For rotary and laser engraving
- High detail laser engraving



APPLICATIONS

Control panels, legend plates, award plates, interior and exterior signage

SPECIFICATIONS

Finish	Satin or Glossy
Composition	Aluminum
Engraving depth	0.1 mm (.004")
Full sheet	610 mm x 610 mm (24" x 24")
Half sheet	610 mm x 305 mm (24" x 12")
Quarter sheet	305 mm x 305 mm (12" x 12")
Other size	-

CAPABILITIES

Interior	■
Exterior	■
Shear	■
Saw	■
Silk screen	■
Hot stamp	-
Heat bending	-
Scratch resistant	■
Flexible	-
Break resistant	■
UV resistant	■
Min. temp.	0°C (30°F)
Max. temp.	82°C (180°F)

TECH TIPS

Strong anodisation for a durable protection of the material.

You can use Gravograph recommended paint to color any GravoXal™ engraving. See p.67.

Aloxide may be used to color glossy plates (small characters) after rotary engraving.

			0.5 mm (.020")**
			0.8 mm (1/32")
			1.6 mm (1/16")
satin red		34526	34519
satin blue		34496	34495
satin silver		34624	34617
			34619
glossy gold		34594	34592
satin black		34454	34452
			34453

Sold in North America Only
Silver colors are anodised on both sides during the continuous anodisation process.
Protective film on one side.
Due to the process, there can be stains in the corners of aluminum sheets.
* Laser engraving on colored materials. The engraving contrast may vary according to the color.
** Sheet size 24"x12" for .020".



Printed colors for indication only. Cannot serve as a substitute for real material sample.
The dimensions indicated represent our minimal commitment.
Anodising process may produce slightly different colors from one batch to another.

