

Warrantee

One (1) Year Limited Warranty

Subject to the limitations set forth below, Nightowl Stage Lighting hereby represents and warrants that the components of this product shall be free from defects in workmanship and materials, including implied warranties of merchantability or fitness for a particular purpose, subject to normal use and service, for one (1) year the original owner from the date of purchase.

Retailer and manufacturer shall not be liable for damages based upon inconvenience, loss of use of product, loss of time, interrupted operation or commercial loss or any other incidental or consequential damages including but not limited to lost profits, downtime, goodwill, damage to or replacement of equipment and property, and any costs of recovering, reprogramming, or reproducing any program or data stored in equipment that is used with our products. This guarantee gives you specific legal rights. You may have other legal rights which vary from country to state. Some country do not allow limitations on how long an implied warranty lasts, so the above limitation may not apply to you.

Returns

Returned merchandise must be sent prepaid and in the original packing. Package must be clearly labeled with a Return Merchandise Authorization Number (RMA #).

For repair and warrantee service contact contact Nightowl Stage Lighting at NightowlStageLighting.com for an RMA number and shipping instructions. Include a phone number in case we need to speak to you in person. Our website contains all up to date contact information.

Claims

Damage incurred in shipping is the responsibility of the shipper; therefore, the damage must be reported to the carrier upon receipt of merchandise. It is the customer's responsibility to notify and submit claims with the shipper in the event that a fixture is damaged due to shipping. Any other claim for items such as missing component/part, damage not related to shipping, and concealed damage, must be made within seven (7) days of receiving merchandise. We will be happy to assist you with your shipping claim should there be an issue.



USER MANUAL

9*15W RGBWA 6in1 LED aluminium outdoor par light



Nightowl Par64-LED

Technician before replacement. The projector has thermal protection device that will switch off the projector in case of overheating, should this occur, check if the fans work normally or fan and fan shield are blocked by dust. If the projector not operational, call a qualified technician. After cleaned and repaired, the projector can be restarted.

Any maintenance work should only be carried out by qualified technicians.

KEEPING THE PROJECTOR CLEAN

It is definitely necessary to keep a projector clean for its reliable use. Cooling fans and their shield should be cleaned every 15 days. LED lamps, lens and cover should be cleaned regularly for optimized light output.

Cleaning frequency depends on how often a projector is used and its operational environment. A soft cloth and typical glass cleaning products should be used in cleaning. It is recommended to clean the external optics at least once every 20 days.

Do not use any organic solvent, e.g. alcohol, to clean the housing of the apparatus.

Troubleshooting

PROBLEM	ACTION
The projector can't be started	> Power Cable not connected well
	> Power supply damaged or not connected well, a qualified Technician should be required
	> Control board not connected well and a qualified Technician should be
The lamp can be started, but LED lamps are off and not controlled	> LED boards not connected properly, a qualified technician is needed
A projector's lamps are on but it doesn't respond to the controller	> Make sure that the projector's start address is correctly set
	> Replace or repair the DMX cable.
The beam appears dim and Its brightness slows sharply	> Ambient temperature too high which result in a projector overheating, necessary ventilating measures needed.

Testing mode: press up/down button to select sound control and auto mode.

When its language selection status, press up/down button to select Chinese or English.

DMX Mode

When operating in DMX mode (detected when DMX cable is plugged in to a DMX controller) the control panel will only be used for DMX starting address and the light will be controlled using 4/8DMX channels.

When you daisy chain multiple units, a DMX line terminator is highly recommended to prevent erratic behavior.

DMX 512 Control Channels:

6 / 10 Channels:

Channel	Function	No.
CH1	RED	Red dimmer, (0-255) linear dimming, the brightness is from dark to bright.
CH2	Green	Green dimmer, (0-255) linear dimming, the brightness is from dark to bright.
CH3	Blue	Blue dimmer, (0-255) linear dimming, the brightness is from dark to bright.
CH4	White	White dimmer, (0-255) linear dimming, the brightness is from dark to bright.
CH5	Amber	Amber dimmer, (0-255) linear dimmer, the brightness is from dark to bright.
CH6	UV	UV dimmer, (0-255) linear dimmer, the brightness is from dark to bright.


DMX 512 Control Channels		
1	Dimmer	Linear Dimmer Dark to Bright
2	Strobe	Slow to Fast
3	Function	0-50 DMX 8 Channel Control 51-100 Quick Jump 101-150 Gradual Change 151-200 Pulse Change 201-255 Sound Activated
4	Speed	Slow to Fast
5	Red	Linear Dimmer Dark to Bright
6	Green	Linear Dimmer Dark to Bright
7	Blue	Linear Dimmer Dark to Bright
8	White	Linear Dimmer Dark to Bright
9	Amber	Linear Dimmer Dark to Bright
10	UV	Linear Dimmer Dark to Bright

Always disconnect a projector from the POWER when not in use or before cleaning or any

Stand Alone or Master/Slave Mode

LED Display Screen Operation:

Display:



LED Display Screen Function:

Menu Functions		
No.	Display	Function
1	D0001	9CH DMX Starting Address (001-512)
2	A0001	5CH DMX Starting Address (001-512)
3	CC50	Quick Jump 8 Color Chase (Speed 1-99)
4	CP50	Gradual Change 8 Color Chase (Speed 1-99)
5	DE50	Pulse Change 8 Color Chase (Speed 1-99)
6	BEBE	Sound Activated
7	R220	Red Preset (Level 0-255)
8	G220	Green Preset (Level 0-255)
9	B220	Blue Preset (Level 0-255)
10	W220	White Preset (Level 0-255)
11	Y220	Yellow Preset (Level 0-255)
12	U220	UV Preset (Level 0-255)

Thank you for purchasing a *Nightowl* **Par64-LED**. These Mpar cans will provide you will years of trouble free service and allow you to be far more flexible and innovative due to their color mixing capabilities, low power consumption, and the variety of control options.

To optimize the performance of this product, please read these operating instructions carefully to familiarize yourself with its basic operations. These instructions contain important safety information regarding the use and maintenance of this unit. Please keep this manual for future reference.

Safety and Proper Use

- 0 When unpacking and before disposing of the carton check there's no transportation damage before using the projector. Should there be any damage caused by transportation, consult your dealer and do not use the apparatus.
- 0 The projector is for indoor use only, IP20. Use only in dry locations. Keep this device away from rain and moisture, excessive heat, humidity and dust. Do not allow contact with water or any other liquids.
- 0 DO NOT mount the projector directly onto in amnable surface
- 0 The projector is only intended for installation, operation and maintenance by qualited personnel.
- 0 The projector must be installed in a location with adequate ventilation, at least 50cm from adjacent wall surfaces. Be sure that no ventilation slots are blocked.
- 0 Do not project the beam onto in amnable surfaces, minimum distance is 5m
- 0 Avoid direct exposure to the light from the lamp. The light is harmful to the eye. Do not attempt to dismantle and/or modify the projector in any way.
- 0 Electrical connection must only be carried out by qualited personnel.
- 0 Before installation, ensure that the voltage and frequency of power supply match the power requirements of the projector. It is essential that each projector is correctly earthed and that electrical installation conforms to all relevant standards.
- 0 Keep a projector's optical system clean. Do not touch LED lens with bare hands.
- 0 The projector should always be installed with a secondary safety . A safety cord is supplied for this; it should be attached as shown in "installing the projector" section.
- 0 Shields and lens shall be changed if they have become visibly damaged to such an extent than their effectiveness is impaired