

TORQUE LINK

SMART SENSOR TECHNOLOGY



MINIMAL LOSS OF HEADROOM

CLOUD STORAGE

VIEW PILE LOGS ANYTIME, ANYWHERE





THE HARDWARE

Fabricated for serious jobs, our sleek designs protect the internals, and can accomodate most drives in the field.



Machined from SOLID BILLET

Ensuring maximum strength



Off-the-Shelf Batteries

Up to 400 hours working time



Bluetooth (BLE)

No loss of connection with high quality signal





TORQUE SPOOLS

INQUIRE FOR BOLT MEASUREMENT

MODEL	TORQUE	DIAMETER	HEIGHT
SP-030	30K	9"	7"
SP-070	70K	10.25"	8"
SP-250	250K	11"	11"
SP-375	375K	11"	11"



TORQUE HUBS

MODEL HEX INPUT		SPECS	
HB-030-2HX	2"	TORQUE RATING	30K
HB-030-2.5HX	2.5"	FLANGE	9"
HB-030-2.625HX	2-5/8"	BOLT PATTERN	5-1/4", 7-5/8"
HB-030-3HX	3"		

HB-070: 100mm (4") SQUARE INPUT HUB



TORQUE LINKS (M-F)

MODEL

MF-030-2HX MF-030-2.5HX MF-030-3HX

SPECS	
TORQUE RATING	30K
LENGTH (HOLE TO HOLE)	9-1/8"



70K RATED

FEATURES

