



Two-hand grease gun-ZHFP

M 10 x 1-PZ-MU

Item number: 12 851
EAN: 4103810128516
Discount group: A

Technical data

Connection discharge side: M 10 x 1
 Diameter of grease piston (mm): 10
 Max. delivery pressure (bar): 400
 Burst pressure system (bar): 850
 Burst pressure grease gun head (bar): 1200
 Delivery rate stroke (cm³): 2,2
 Filling: 500-g-screw-in cartridge (12 524)
 Lacquering hand levers: black, RAL 9005
 Colour handgrips: black, RAL 9005
 Dimensions LxWxH (mm): 380 x 185 x 30
 Weight (kg): 1,088

Specification

- With hose bracket (86 961 100)
- Grease gun head, zinc die casting Z 410
- Ball seat valve, galvanized (85 589)
- High pressure hose, M 10 x 1 male, 11 x 300 mm, with sealing ring (12 655 828)
- Precision machined coupler, 4 claws, M 10 x 1 female (12 643)
- Sales package, with Bar code

Special notes

- Particularly suitable for long-term and high-performance lubricating greases, even at low temperatures
- Supports grease from penetration grade according to ASTM-mill penetration (10⁻¹ mm): NLGI 3 till 10°C
- Ergonomic contoured safety handgrip
- Extended product lifetime based on an optimal combination of zinc (grease gun head) and polished steel (reciprocating)
- Unmatched surface Ra (0,4 µm) and tolerance (6 µm) of the piston tube for the main piston - no dummy apparent lubrication
- Optimal leverage for operating the hand lever, thus the force required for lubrication is as low as possible
- All screw connections are sealed
- Quick exchange of cartridges
- Environmental friendly, cartridge can be emptied completely
- Filling level and type of grease visible

Packaging

Dimensions LxWxH (mm): 381 x 181 x 31
 Weight including package (kg): 1,19
 Pallet Quantity (h = 1,2 m): 300 pcs.
 Packing unit: 1,0