

# NOMAH™ Installation Instructions

1. Buckle crotch buckle on car seat- this step helps ensure the harness webbing does not get twisted.

~A video tutorial can be found at [https://youtu.be/jptK\\_NbfNXM](https://youtu.be/jptK_NbfNXM)

2. Facing the back of the car seat you will see a "Y" clip with harness webbing attached.



3. Unhook the harness webbing (strap) from the "Y" clip.



4. Pull harness webbing (strap) through slots on front of car seat.



5. Remove chest clip pieces and set aside.




6. Begin threading the harness webbing (strap) through the NOMAH beginning on the bottom slot and putting the webbing in through the back pulling towards you.



7. Thread the harness webbing through the top slot on the NOMAH and pull away from you to tighten.



8. Replace the chest clip ensuring that the harness webbing is on top of the NOMAH and there are no twists in the harness webbing.



9. Thread the harness webbing back through the slot. (note- you may need to adjust the headrest height to easily access the slot).



10. Ensuring there are no twists in the harness webbing, hook the loop of the harness webbing back onto the "Y" clip.



11. Repeat steps 3-10 using the other harness webbing (strap).

12. Feel safe knowing your child can no longer push their chest clip down.



In no event, regardless of cause, shall KCI Products LLC be liable for any indirect, misuse, special, incidental, punitive or consequential damages of any kind not limited to injury or death. KCI Products LLC will not be held liable under breach of contract, negligence, strict liability or otherwise.