

	Standard	Compact
Applications	• Dispenser Control • Wetstock Control • Price Pole Control • Payment Control • Attendant Tagging • AVI • Performance Monitoring • Sudden Loss Detection • Veeder-Root Data Logger • 3rd Party Terminals	• Dispenser Control • Wetstock Control • Price Pole Control • Payment Control • Attendant Tagging • AVI • Performance Monitoring • Sudden Loss Detection • Veeder-Root Data Logger • 3rd Party Terminals • IFSF Car Wash

		• IFSF Car Wash • Cloud Connector	
Central Processor Board	CPB539	CPB505-2	
CPU Type	ARM	ColdFire MCF5307	
Flash	(Quad	(Single core)	
RAM	core)	16 MB	
Operating System	4 GB	4 MB (SRAM)	
	RAM	Proprietary	
	Linux		
Port Types & Number			
DSB		6	3
DMB		2	1
Ethernet		2	1
SBC options available		KIT441: CPU: Intel Atom, 1.6GHz RAM: 1GB Flash: 4GB card	KIT441: CPU: Intel Atom, 1.6GHz RAM: 1GB Flash: 4GB card Requires double-door accessory.
Dimensions (mm)		600 x 200 x 124	337 x 200 x 100

Max. number of single size modules	14	6
------------------------------------	----	---