

2026 MONSTER THUNDER BOMBER RULES

A Monster Thunder Bomber Series event is a competitive racing event, which is intended to be conducted and officiated in accordance with the rules herein (the 2026 Monster Thunder Bomber Series rule book). These rules provide guidelines for all events. The rulebook may be amended from time-to-time and special rules may be published and/or adjusted at any event with the participants receiving prior notification. By participating in these events, all participants agree to comply with these rules and regulations. The rules are not intended to express or imply the warranty of safety of hardware or software as a result of publication of, or compliance with the rules and regulations as stated herein. The rules are intended to offer a guideline for the conduct and officiating of an event. The series director shall be empowered to permit any reasonable and/or appropriate amendment from any of the specifications and/or procedures herein, or impose any further restrictions that in their opinion does not alter the minimum acceptable requirements. Revisions to the rules are not intended to express or imply the warranty of safety shall not result from any such deviation or restriction of the specifications, rules and/or procedures. Any interpretation of, deviation from, these rules herein, are left to the discretion of the racing officials and their jurisdiction is final. It is ultimately the obligation of each participant to ensure their conduct and equipment complies with all of the applicable rules, as they may be amended from time-to-time.

Thank you for your continued support,

Scott Morgan Monster Thunder Bomber

GENERAL RULES ARE AT THE DISCRETION OF THE TRACK FOR WEEKLY RACING. RACE PROCEDURES WILL APPLY AT ALL SERIES RACES. (1.0 TO 7.0)

1.0 General Rules

1. Drug and alcohol consumption will not be tolerated. Those found under the influence while racing will not race and could face fines and/or suspension.
2. Everyone must have a 1099/w9 on file to participate
3. Anything that could be considered unsportsmanlike conduct will not be tolerated.
 - a. This includes, but is not limited to, fighting and verbal altercations. This also includes social media networks, and will be left up to the discretion of the series staff.
4. Those using inappropriate and/or foul language towards another competitor or fan may receive one warning, after that you will be disqualified, with no points or money being awarded.
5. Cursing or assaulting any Monster Thunder Bomber Series or track official will result in an automatic disqualification, and/or suspensions/penalties. This will be left up to the series director's discretion.
6. All cars entered into Monster Thunder Bomber Series competition must pay an entry fee to Monster Thunder Bomber Series prior to technical inspection.
7. Media, streaming and all other digital rights are reserved to Monster Thunder Bomber Series and Monster Thunder Bomber Series media designee(s)
8. The rules and/or regulations set forth herein are neither expressed nor implied warranty of safety from publication of or compliance with rules and/or regulations. These rules are intended as a guideline for the conduct of Monster Thunder Bomber Series sanctioned street stock division events, and are in no way a guarantee against injury or death to participants, spectators, or officials.
9. The rules and/or regulations will apply to all Monster Thunder Bomber Series sanctioned events.

10. Monster Thunder Bomber Series officials shall have full authority over said sanctioned events, and in the event of any dispute, the head official's decision will be final.
11. All competitors and cars are subject to inspection by Monster Thunder Bomber Series technical inspectors or their representatives at any time during any event.
12. Monster Thunder Bomber Series, and its officials and representatives reserve the right to confiscate any suspicious or deemed illegal parts or components.
13. Monster Thunder Bomber Series reserves the right to alter or amend these rules and/or regulations in the interest of fair competition, efficient completion of an event, or for safety. all official's decisions are final.
14. **Radios are not permitted. MAY RUN MIRROR**
15. Monster Thunder Bomber Series reserves the right to refuse any car/competitor from participating in a Monster Thunder Bomber Series sanctioned event.

2.0 Racing Rules

1. Everyone must be at the venue at the start of qualifying, to participate in the A-Main and must be present on day one of any two day event to receive any provisional.
2. Anyone missing the driver's meeting is subject to penalty.
3. Drivers must stay at a moderate pace speed during all starts and restarts, until green. Drivers jumping the start will be penalized two positions for every position they advance.

3.0 Points

1. 2026 Points fund criteria
 - a. Drivers must compete in 80% of events during the 2026 Monster Thunder Bomber Series season to be eligible to receive banquet awards or special category awards for the 2026 championship.
 - b. Drivers must attend the banquet to receive awards and money.
2. Earning points
 - a. Every driver receives points as long as they pay the membership fee, entry fee and compete in (at least) time trials, a heat race, or a b-main.

4.0 Membership

1. All drivers participating at Monster Thunder Bomber sanctioned tracks and events must purchase an annual membership at a cost of \$50 per year. This membership makes the driver eligible for points fund monies and contingency awards. A temporary membership will be available at a cost of \$10 per race.
2. Memberships are considered licenses and can be revoked at any time at the series discretion.
3. A minimum of \$50 from series race entry fees go to Monster Thunder Bomber Series in order to support the end of the year points payout.

5.0 Rules

1. ALL LEAD MUST BE SECURELY FASTENED WITH BOLTS AND/OR WEIGHT CLAMPS. DUCT TAPE AND ZIP TIES ARE NOT ACCEPTABLE. MUFFLER CLAMPS ARE NOT ACCEPTABLE.
2. LEAD MUST BE PAINTED WHITE WITH CAR #
3. MUST HAVE WORKING FIRE EXTINGUISHER IN CAR, UNLESS RUNNING FIRE SUPPRESSION SYSTEM.

4. MUST HAVE SFI APPROVED 5 POINT HARNESS THAT IS IN DATE. (3 YEARS OLD MAXIMUM)
5. MUST HAVE A WORKING RACECEIVER/NITRO BEE/SWITCH AT ALL TIMES WHILE ON THE RACING SURFACE. TUNED TO 454.000
6. FULL CONTAINMENT SEATS AND HEAD RESTRAINT RECOMMENDED AT ALL TIMES.
7. CARS DEEMED UNSAFE TO RUN OR THAT FAIL PRETECH WILL NOT BE ALLOWED TO RACE AT THE TECH OFFICIALS' DISCRETION.
8. RACING SEATS REQUIRED, MUST FIT DRIVER, BE SFI APPROVED, AND MUST BE BOLTED TO ROLL CAGE
- .9. NO ALUMINUM OR TITANIUM CAGES OR TUBING PERMITTED. ALL TUBING MUST BE A MINIMUM OF 1 1/2 INCHES AND A MINIMUM OF .095 WALL THICKNESS. THREE BARS IN DRIVER'S SIDE MANDATORY, TWO BARS IN RIGHT SIDE MANDATORY. MUST HAVE A MINIMUM OF 1 INCH BAR, .083 WALL THICKNESS IN HALO SECTION RUNNING EITHER FRONT TO REAR OR DIAGONAL ACROSS.

5.1 WEIGHT:

WEIGHT MUST BE POSTED CLEARLY ON BOTH SIDES OF A-PILLAR OR HOOD.

1. 3200LBS MINIMUM WEIGHT AT ALL TIMES.
2. NO WEIGHT BREAKS, NO BURNOFF.

5.2 WHEELBASE:

1. STOCK WHEELBASE FOR CHASSIS BEING RAN.
2. ANY CHASSIS WITH A WHEELBASE OTHER THAN +/- 1IN FOR MAKE AND MODEL WILL NOT BE ALLOWED
3. NON-LEAF SPRING CARS MAY RUN TUBING SQUARE OR CIRCULAR FROM BUCKETS TO BUMPER.
4. NO CARS UNDER 108IN WHEELBASE
5. MONTE CARLOS, CAMAROS, NOVAS ETC PERMITTED
6. REAR WHEEL DRIVE VEHICLES ONLY.
7. NO STRUT OR COILOVER TYPE CARS
8. NO CUTTING OR SHORTENING OF WHEELBASE/FRAME IN ANY WAY UNLESS OTHERWISE STATED.

10.3 BODY NON-PROTEST ITEM GOVERNED BY MONSTER OFFICIALS: THOUGH THEY MAY NOT BE PROTESTED THE BODIES MAY BE OBSERVED,

MEASURED, ETC. AS NECESSARY. IF MONSTER OFFICIALS DO NOT APPROVE, YOU WILL BE ASKED TO CHANGE IT, ADD WEIGHT OR ANYTHING

DEEMED NECESSARY BY THE OFFICIALS. AFTERMARKET DIRT BODIES ALLOWED. ALL BODIES SHOULD CARRY ORIGINAL BODY LINES WITHIN REASON.

CAR MUST BE NEAT IN APPEARANCE. STOCK STEEL BODIES OR ALUMINUM AFTERMARKET BODIES ALLOWED. BODY WIDTH MAY NOT EXCEED 72" AT THE TOP OF DOORS OR QUARTERS AND 75" AT THE BOTTOM OF DOORS AND QUARTERS.

1. ROOF:

a. THE MINIMUM ROOF SIZE IS 46" X 50". 4 INCH MAX RAKE FROM FRONT TO REAR/LEVEL SIDE TO SIDE. IF RUNNING A WAGON BODY MUST STILL FOLLOW THE RULE OF NO MORE THAN 4' OF RAKE FROM FRONT TO REAR AND CAN NOT RUN ANY SPOILER

2. NOSE:

- a. NO FINS OR FLARES EXTENDING OVER THE HOOD OR FENDERS OF THE CAR. NO LATE MODEL FENDER FLARES.
- b. THIS IS A THUNDER BOMBER CLASS; CARS SHOULD BE SIMILAR TO THUNDER BOMBERS.
- c. NO MD3, WEDGE OR LATE MODEL STYLE NOSES. ALL NOSES SHALL BE MOUNTED RELATIVELY STRAIGHT UP AND DOWN. DO NOT LAY THE NOSES BACK TO CREATE A WEDGE NOSE.
- d. NOSES SHALL BE MOUNTED AT A CONSISTENT ANGLE FROM LEFT TO RIGHT.

3. TAILPIECE:

- a. TAILPIECE REQUIRED.
- b. BARS MAY NOT EXTEND BEYOND INSIDE OF REAR TIRES. MUST BE CAPPED OR TURNED IN ON THE ENDS
- c. THE TAILPIECE MUST EXTEND FROM THE TOP OF THE DECK TO THE BOTTOM OF THE FRAME HORNS. THE TAILPIECE MUST BE MOUNTED VERTICALLY WITH NO SLANT. THE TAILPIECE MUST ALSO EXTEND FROM QUARTER PANEL TO QUARTER PANEL. NO HOLES OR FLAPS. MIN OF 16 INCHES

4. COCKPIT:

- a. MUST RUN COMPLETE, ENCLOSED COCKPIT.
- b. MINIMUM OF 22 GAUGE SHEET METAL OR .040 ALUMINUM.
- c. IT IS RECOMMENDED THAT THE DRIVERS DOOR IS PLATED WITH .25" STEEL.
- d. 13" MINIMUM OPENING FRONT SIDE AND REAR OF DRIVER.
- e. FIRE WALL REQUIRED BETWEEN DRIVER AND FUEL CELL. MINIMUM OF 22 GAUGE STEEL/ SHEET METAL.

5. SPOILER:

- a. ONE (1) MAXIMUM 6"X60" SELF SUPPORTING SPOILER PERMITTED ON THE REAR OF THE CAR. **MUST BE CENTERED ON DECK OF CAR. CAN NOT SLIDE TO THE LEFT OR THE RIGHT.**
- b. NO ADDITIONAL SPOILERS OR FINS ANYWHERE ON THE CAR. **THIS MEANS ROOF TOO**
- c. SPOILER MUST BE MOUNTED AT THE SAME ANGLE LEFT TO RIGHT
- d. 1 INTERIOR ROCK/MUD GUARD ON THE RIGHT SIDE OF THE DRIVER WILL BE PERMITTED UNDER THE FOLLOWING CRITERIA. MUST BE MOUNTED ON THE RIGHT SIDE OF THE DRIVER AND CAN NOT BE TALLER THAN THE HEIGHT OF THE DASH. THIS ROCK GUARD MUST BE MOUNTED TO THE DECK AND MUST BE MOUNTED FROM FRONT TO BACK; WITH A MAXIMUM OF 2 INCHES OF SKEW FROM LEFT TO RIGHT.

6. DECK HEIGHT

- a. THE MAXIMUM DECK HEIGHT IS 42 INCHES. THERE IS NO TOLERANCE FOR THIS MEASUREMENT.
- b. NO MORE THAN 4 INCHES OF DROP ANYWHERE ON THE INTERIOIR DECK FROM HIGHEST POINT OF THE BODY.

7. HOOD

- a. BREATHER CAN EXTEND THROUGH THE HOOD. DOES NOT HAVE TO BE BOXED IN.
- b. NO ADDITIONAL HOLES IN HOOD EXCEPT HOOD PIN HOLES.

8. DOORS AND QUARTER PANELS

- a. DOORS CAN BE FLAT SIDED. STAKT PANELS ARE LEGAL
- b. NO BODY SKEW FROM LEFT TO RIGHT LIKE A LATE MODEL. ALL PANELS MUST BE RELATIVELY STRAIGHT FROM THE FRONT OF THE CAR TO THE REAR OF THE CAR.

9. SIDE SKIRTS

- a. MINIMUM OF 5 INCHES AT RIDE HEIGHT FROM PLASTIC TO GROUND.

5.3 CHASSIS & SUSPENSION:

1. MUST HAVE STOCK FIREWALL AND FLOOR PAN EXTENDING FRAME RAIL TO FRAME RAIL AND FROM THE DECK TO THE FRAME RAIL. FLOOR PAN MUST BE TO BACK SEAT AREA
- a. FIREWALLS AND FLOOR PANS MUST BE IN STOCK LOCATION.
2. FRONT AND REAR SUSPENSION COMPONENTS MUST REMAIN STOCK OR OEM STOCK TYPE FOR TYPE OF CHASSIS RUNNING, UNLESS OTHERWISE STATED. THIS INCLUDES BUT IS NOT LIMITED TO DRAG LINK, TIE RODS, SPINDLES, IDLER ARM.
3. STEERING MUST BE STOCK TYPE/OEM REPLACEMENT.
4. QUICKENERS AND COLLAPSIBLE STEERING SHAFTS ALLOWED.
5. STOCK LENGTH BOTTOM REAR TRAILING ARMS ONLY. UPPER REAR TRAILING ARMS MAY BE SHORTENED FOR PINION ANGLE. AFTER MARKET BUSHING TYPE ONLY OK
6. A-FRAMES - UPPER CONTROL ARMS MAY BE TUBULAR STEEL OR MODIFIED OEM. NO ADJUSTABLE A ARMS
7. LOWER CONTROL ARM MUST BE STOCK TYPE FOR FRAME USED, MUST REMAIN UNALTERED AND IN STOCK LOCATION.
8. ANY STOCK TYPE BALL JOINT PERMITTED. SCREW IN OK. (MAY NOT BE LONGER, BIGGER, SMALLER, REBUILDABLE, ADJUSTABLE ETC.) $\frac{1}{4}$ " TOLERANCE.
9. SOLID RUBBER OR STEEL BUSHINGS ALLOWED. MONOBALLS NOT PERMITTED
10. FRONT SHOCKS MUST BE STOCK MOUNT; MAY MOVE UP OR DOWN FOR TRAVEL 3" MAXIMUM. BRACKETS MUST NOT HAVE ANY EXTRA HOLE FOR ADJUSTMENTS.
11. NO ENGINE SET BACK. RADIATOR MUST BE IN STOCK LOCATION.
12. BILSTEIN AK1043 FRONT AND AK1044 (MONTE CARLO), AK1054 (CAMARO, NOVA) REAR ARE THE ONLY SHOCK ALLOWED.
13. 1 BILSTEIN AK1044 OR AK1050 SHOCK PER WHEEL MOUNTED BEHIND THE REAR END ONLY.
14. STOCK REAR FRAMES MAY BE REPAIRED FROM CENTER OF REAR END HOUSING TO REAR BUMPER WITH SQUARE TUBING OR 1 3/4", .095 MINIMUM THICKNESS ROUND TUBING.
15. NO PANHARD BARS OR Z BARS OF ANY TYPE.
16. NO UNDERSLUNG REAR SUSPENSION ALLOWED.
17. ADJUSTABLE FRONT AND REAR SPRING BUCKETS ALLOWED. ONLY ONE PER CORNER, MUST BE MOUNTED FLAT AND CENTERED TO REAREND. NO WEIGHT JACKS OR JACK BOLTS
18. A-FRAMES - UPPER CONTROL ARMS MAY BE TUBULAR STEEL OR MODIFIED OEM. NO ADJUSTABLE A ARMS
19. MODIFIED OEM UPPER A ARMS OR MAY MOVE PERCHES.
- a. 1 HOLE PER SIDE ONLY ON THE A-FRAME TOWER. NO A-ARMS WITH PILLS. MAY NOT CUT SPRING POCKET OR CHASSIS.
20. ONE SPRING RUBBER PER SPRING ONLY. NO PROGRESSIVE SPRINGS, NO DUAL RATE SPRINGS, NO STACK SPRINGS. MAX 13 INCH. MUST RUN SAME LENGTH SPRING ON BOTH SIDES.
21. RACING SPRINGS AND/OR ADJUSTABLE SWAY BAR PERMITTED. (STOCK TYPE SWAY BARS ONLY)
22. ALL SUSPENSION MOUNTING POINTS MUST BE IN STOCK LOCATION.

23. X BRACING OK

5.4 IGNITION:

1. STOCK TYPE HEI DISTRIBUTOR, MODULE, COIL ETC. (NO MAGNETOS, CRANK TRIGGER SYSTEMS, OR IGNITION BOXES) MUST HAVE VACUUM ADVANCE
2. FIRING ORDER MUST REMAIN STOCK. (CHEVROLET: 1-8-4-3-6-5-7-2)
3. ONE 12 VOLT BATTERY ONLY

5.5 CARBURETOR:

1. HOLLEY #1850 , STOCK OEM PRODUCED 2 OR 4 BARREL (QUADRAJET), **HOLLEY 4777 \$750**
BUY RULE ON CARBURETOR
 - a. **CARBURETORS MUST REMAIN STOCK OR BOX STOCK.**
2. CARBURETORS WILL BE CHECKED WITH GO-NO-GO GAUGES TOP TO BOTTOM. MUST BE STOCK
3. MAY RUN 1 MR. GASKET PN#1932 CARBURETOR SPACER WITH THE HOLLEY .040" TOLERANCE (AT NO POINT MAY SPACER EXTEND INTO INTAKE MANIFOLD AREA) WITH 2 STANDARD THICKNESS CARBURETOR GASKETS, .070" MAXIMUM THICKNESS.
4. ALL HOLLEY CARBURETORS MUST HAVE CONVENTIONAL STYLE FLOATS ALONG WITH NEEDLES AND SEATS. NO INDIVIDUAL CYLINDER TUNING OR EQUIVALENT ALLOWED.
5. ALL CARBURETORS MUST HAVE CONVENTIONAL "HOLLEY-STYLE" STRAIGHT OR DOWN LEG BOOSTERS, NO EXCEPTIONS.
6. ALL CARBURETORS MUST BE BOX STOCK WITH CHOKE FLAP REMOVAL ONLY. MAY CHANGE JETS AND POWER VALVE, CHOKE HORN MUST REMAIN INTACT
 - .a. NO PORTING OR POLISHING. MAY NOT CHANGE METERING BLOCKS OR ANY OTHER INTERNALS UNLESS OTHERWISE STATED. NO 4 CORNER IDLE SCREW.
7. NO COLD AIR BOXES.
8. NO HEAT SHIELDS AROUND CARBURETOR. DUST SHIELD MOUNTED TO AIR FILTER BASE OK.

5.6 EXHAUST SYSTEM

1. MILD STEEL HEADERS ONLY. NO MERGE COLLECTOR HEADERS. STANDARD 4 INTO 1 ONLY.
2. X PIPES, TRY Y'S, OR OTHER MERGE STYLE HEADERS NOT PERMITTED.
3. NO TURNDOWNS, NO MUFFLERS, NO BAFFLES BUT 21 INCH EXTENTION ALLOWED. MUST BE SAME DIAMETER AS COLLECTOR, STRAIGHT AND NO RESTRICTIONS
4. 3 OR 3 1/2 INCH COLLECTOR ONLY
5. HEADER CLAIM: \$500
 - a. CAR CLAIMING MUST FINISH IN THE TOP 5 AND ON THE LEAD LAP. CLAIMS MUST BE MADE TO TECH OFFICIAL WITHIN 5 MINUTES OF SCALING.
 - b. NO REVERSE CLAIMS WILL BE PERMITTED.
 - c. REFUSAL TO ALLOW THE CLAIM WILL RESULT IN THE DRIVER LOSING ALL POINTS AND MONEY FOR THAT EVENT AND FACE THE FOLLOWING PUNISHMENT:
 - i. FIRST OFFENSE - 7 DAY SUSPENSION FROM ANY MONSTER SANCTIONED EVENT AND \$250 FINE

ii. SECOND OFFENSE - 30 DAY SUSPENSION FROM ANY MONSTER SANCTIONED EVENT AND \$500 FINE

iii. THIRD OFFENSE - 365 DAY SUSPENSION FROM ANY MONSTER SANCTIONED EVENT AND \$1000 FINE

5.7 FUEL SYSTEM:

1. 110 RACING FUEL OR PUMP GAS (87,89,93) ONLY. NO MIXING OF PUMP GAS AND RACING GAS. NO E85.

a. NO ADDITIVES OR OXYGENATORS.

2. STOCK TYPE FUEL PUMP ONLY.

3. FUEL IS SUBJECT TO LABORATORY TESTING AND FUEL MAY NOT CONTAIN ANY ADDITIVES.

a. THE SPECIFIC ELEMENTS WHICH WILL BE SEARCHED FOR INCLUDE: PROPYLENE OXIDE, ALCOHOLS (ALL TYPES), ALDEHYDES, AMINOBIPHENYL, BENZENE (IN EXCESS OF EPA LIMIT), BENZIDINE, BERYLLIUM COMPOUNDS, BROMINE COMPOUNDS, BUTADIENES, CHLORINATED COMPOUNDS, CHROMATES, DIOXANES, ETHYL ACRYLATE, ETHYLENE OXIDE, HYDRAZINE COMPOUNDS, METHYLENE DIANILINE, NAPHTHYLAMINE, NITROGEN COMPOUNDS (NITROMETHANE, ET AL.), STYRENES, TOLUIDINE AND XYLIDINE. ALSO ADDED THIS LIST WILL BE SUBSTANCES DEEMED TO EXCEED THE THRESHOLD LIMIT VALUES (TLV) OR BIOLOGICAL EXPOSURE INDICES (BEI) AS LISTED BY THE AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS (ACGIH).

b. FUEL MUST MEET SPECIFIC GRAVITY AT ALL TIMES.

c. FUELS MUST MEET MANUFACTURER'S BENCHMARK AT ALL TIMES.

d. GASOLINE OR RACE GAS – FUEL SAMPLES MAY BE TAKEN AND SENT TO AN INDEPENDENT LAB FOR TESTING.

4. SFI CERTIFIED FUEL CELL WITH ROLL-OVER VALVE MANDATORY.

5. STOCK-STYLE FUEL PUMP NO REAR MOUNTED PUMPS

6. IN-LINE FUEL SHUT OFF RECOMMENDED WITHIN REACH OF DRIVER.

5.8 DRIVELINE:

1. ALL CARS MUST HAVE SAFETY LOOP FOR DRIVESHAFT.

a. DRIVESHAFT MUST BE STEEL AND AT LEAST 2" IN DIAMETER

2. SINGLE DISC, STOCK OR STOCK EQUIVALENT CLUTCH OR REPLACEMENT CLUTCH ONLY.

3. CLUTCH MUST HAVE SOLID LINING ONLY. YOU MUST HAVE SPRINGS IN CLUTCH. PRESSURE PLATE MUST BE STOCK OR STOCK REPLACEMENT ONLY (STEEL ONLY). HYDRAULIC THROW OUT BEARING OK.

4. PRESSURE PLATE MUST WEIGH A MINIMUM OF 12 LBS. STEEL ONLY, 10.5" ONLY.

5. FLYWHEEL- GM P/N 14088646 OR STOCK REPLACEMENT. 12.75" DIAMETER. 14 LB. MIN. WEIGHT. SCATTER SHIELD OR 3/16" PLATE AROUND FLYWHEEL AREA-MANDATORY

5.9 TRANSMISSION:

1. GM OEM SAGINAW 3 SPEED MANUAL TRANSMISSION ONLY.

a. ALL WORKING GEARS FORWARD & REVERSE.

b. ALL FORWARD GEARS MUST BE HELICAL CUT TEETH.

2. YOU MAY RUN 350 OR 400 TURBO AUTOMATIC WITH OEM WORKING TORQUE CONVERTER.

- a. FLEX PLATE MUST BE GM #14088765 OR GM #14088761.
- 3. NO POWER GLIDES.
- 4. TRANSMISSION INTERNAL PARTS CAN NOT BE POLISHED, COATED, OR LIGHTENED.
- 5. GEARS MUST BE STOCK FOR TRANSMISSION

.

5.10 REAR END:

- 1. STOCK MOUNTING ONLY
 - a. NO ADDITIONAL MOUNTING HOLES, SLIDERS OR ORIFICES.
- 2. NO LEAD MOUNTED ON REAR ENDS.
- 3. ANY RATIO REAR GEAR. MUST BE OEM, NO LIGHT WEIGHT, OFFSET, SCALLOPED OR POLISHED PARTS.
- 4. TRAILING ARM BRACKETS ON THE REAR END MUST BE SYMMETRICAL FROM LEFT TO RIGHT.
- 5. ANY STOCK TYPE REAR END HOUSING PERMITTED (GM 10-12 BOLTS, OR FORD 9 INCH) IN ANY MAKE OF CAR. FLOATER AXLES PERMITTED. MUST USE STEEL STOCK LUG PATTERN HUBS (5 X 5 OR 5 X 4 3/4 OK). NO WIDE 5 HUBS OR WHEELS. REAR TRAILING ARM MOUNTS AT FRAME OR LEAF SPRING MOUNTS MUST REMAIN UNALTERED AND IN STOCK LOCATION WITH ONE MOUNTING HOLE ONLY. LEAF SPRING CARS MAY HAVE ADJUSTABLE SHACKLES ON REAR. NO SLIDERS. NO CHRYSLER LEAF SPRINGS
- 6. REAR TRAILING ARMS MUST BE STOCK TYPE (MAY BE BOXED FOR STRENGTH AND SAFETY. 2 3/4" MAX FROM BOTTOM OF HOUSING TO CENTER OF CONTROL ARM BOLT. UPPER CONTROL MOUNTS MAXIMUM OF 3 INCHES FROM CENTER OF TOP OF REAREND HOUSING TO CENTER OF MOUNTING BOLTS OR ON FORD 9" HOUSING, 7 3/4" FROM SEAM OF AXLE TUBE TO CENTER OF MOUNTING BOLTS.
- 7. 5 INCH COIL SPRINGS MANDATORY, ANY LEAF SPRING ALLOWED.
- 8. SPRINGS MUST BE CENTERED ON THE REAR END.
- 9. BOTTOM SHOCK LOCATION CAN BE RELOCATED
- 10. MAY RUN AFTERMARKET AXLES. NO BALL SPLINE AXLES. NO GUN DRILLED AXLES.
- 11. ALL COMPONENTS MUST BE STEEL OR CAST.
- 12. NO LIGHTENING OF ANY PARTS.

5.11 BRAKES:

- 1. STOCK TYPE (4-WHEEL DISC APPROVED). BRAKES DO NOT HAVE TO MATCH MAKE OR MODEL OF CAR. MINIMUM OF .810" ROTORS.
 - a. ROTORS IN QUESTION WILL BE CHECKED.
 - b. NO GUNDRILLED OR SCALLOPED ROTORS.
- 2. RACING PEDALS, ADJUSTERS & DUAL MASTER CYLINDERS ARE ALLOWED. MUST HAVE OPERATIONAL 4 WHEEL BRAKE. NO ELECTRIC OR MANUAL SHUT OFF VALVES
- 3. STOCK OEM OR OEM REPLACEMENT BRAKE CALIPERS, STEEL ONLY.

5.12 TIRES & WHEELS:

- 1. TOWEL CITY RECAP (YELLOW SPLIT DOT) ONLY. MUST PUNCH A MINIMUM OF 55 AT ALL TIMES.
- 2. 15X8IN STEEL WHEELS ONLY, ANY OFFSETS PERMITTED, SPACERS PERMITTED.
- 3. GROOVING, NEEDLING AND SIPING NOT PERMITTED.

4. TIRES ARE SUBJECT TO CHEMICAL LAB TESTING, REQUIRED TO CONFORM TO BENCHMARK AT ALL TIMES.
 - a. LAB RESULTS ARE INDEPENDENT AND THE LAB HAS FINAL SAY ON WHETHER THE TIRE HAS BEEN ALTERED.
 - i. IT IS SUGGESTED TO WASH TIRES ONLY WITH WATER. DEGREASERS MAY REMOVE OILS IN THE TIRE RESULTING IN FAILURE TO MEET MANUFACTURER'S BENCHMARK.
 - b. TIRES WILL BE SAMPLED AND ARE EXPECTED TO NOT BE ALTERED WITH ANY CHEMICALS.
 - i. TIRES NOT CONFORMING TO THE BENCHMARK WILL RESULT IN DISQUALIFICATION, LOSS OF POINTS AND PRIZE MONEY AS WELL
1. FIRST OFFENSE – \$500 FINE, SUSPENDED UNTIL FINE IS PAID. TRACK RETAINS \$250.
2. SECOND OFFENSE – \$1000 FINE, SUSPENDED UNTIL FINE IS PAID. TRACK RETAINS \$500.
3. THIRD OFFENSE – INDEFINITE SUSPENSION FROM ALL MONSTER THUNDER BOMBER SERIES EVENTS AND
FINE AT SERIES DISCRETION.

5.13 ENGINE:

NO ALUMINUM ENGINE PARTS AT ANY TIME UNLESS OTHERWISE SPECIFIED

A: BOTTOM END:

1. ANY OEM STOCK SIZE ENGINE - MAX SIZE 362 - .060 OVER BORE MAX.
2. REPAIRED ENGINE PARTS MUST BE APPROVED.
3. ARP ROD BOLTS OK BUT MUST REMAIN STOCK SIZE - 3/8.
4. 1 PIECE REAR SEAL BLOCK OK.
5. NO HIGH-PERFORMANCE ENGINES OR SPECIAL-ORDER PARTS.
6. .060 OVER BORE MAX.
7. STOCK BLOCKS ONLY.
8. *MUST BE STOCK REPLACEMENT LOW COMPRESSION PISTON. CANNOT CUT TOP OF PISTON.
9. NO FLAT TOP 4 EYEBROW PISTON - MUST BE DISHED.
10. SPEEDPRO H423 NCP/DCP, MAHLE 224-3543, SILV-O-LITE 1476HC. REPLACEMENT PISTON OK. NO METRIC RING PACKAGE.
11. ZERO DECK HEIGHT OK
12. NO BOTTOMING OF LIFTERS.
13. STOCK CRANKSHAFT. SCAT 9-10442(915104420)
14. NO KNIFE EDGING OR LIGHTENING, ETC.
15. CAST CRANK MUST WEIGH 48 LBS.
16. NO STROKING OR DESTROKING.
17. JOURNALS MAY BE TURNED NO MORE THAN .060". STOCK REPLACEMENT BEARINGS ONLY
18. ROD WIDTH MAY NOT BE LESS THAN .940. MAY RUN SCAT ROD3-ICR5700P
19. STOCK TIMING CHAIN GEAR SET OR CLOYES C-3023X ADJUSTABLE TIMING CHAIN. NO OFFSET KEY WAYS.

20. BALANCER 6 3/4 BY 1" NO MACHINING.
21. MAY RUN RACING PULLEYS
22. ALUMINUM WATER PUMP ALLOWED.
23. **SERPENTINE PULLEYS - V BELT RACING PULLEYS OK.**
24. AFTERMARKET FUEL PUMP AND FUEL ROD OK.
25. AFTERMARKET POWER STEERING OK.
26. 2 PIECE TIMING COVERS OK.
27. NO REMOTE OIL FILTER OR EVAC SYSTEMS
28. STOCK TYPE PAN WITH BAFFELS OK. NO KICK OUTS

B. HEADS

1. ANY OPEN CHAMBER HEAD OK BUT MUST MEET THE FOLLOWING CRITERIA. \$1200 BUY RULE ON EXISTING HEADS WILL ADD BUY RULE ON NEW STYLE HEADS LATER IN THE YEAR
2. DART 10024360 IRON EAGLE HEADS OK. MUST REMAIN STOCK AS THEY COME INCLUDING VALVE JOB. IF NOT LIKE OUR HEAD IT WILL BE WRONG. **THESE HEADS ARE NOT LEGAL UNTIL JULY 1 2025**
3. STOCK REPLACEMENT SCREW IN STUDS OK MAY PIN THEM
4. MAY RUN AFTERMARKET VALVE COVER.
5. HEADS CANNOT BE LESS THAN 72 CC ON ANY HEAD
6. NO ANGLE MILLING.
7. STOCK OR STOCK REPLACEMENT VALVE FOR MAKE AND MODEL. STEEL VALVES ONLY. STOCK STEM DIAMETER.
8. VALVE SPRINGS CAN BE Z28 SPRINGS.
9. 0.194" MAX WIRE DIAMETER.
10. 2.050" MAX LENGTH.
11. COMP 742 RETAINERS OR STOCK ALLOWED.
12. 3 ANGLE VALVE JOB WILL BE PERMITTED NO COMPETITION VALVE JOB. MAX CUT .250 BELOW THE 45 ON OEMGM HEADS.
13. DO NOT TOUCH THE CAST PORT. NO BOWL CUTTING OR PORT WORK WHATSOEVER. IF ANY MATERIAL IS REMOVED, IT WILL BE CONSIDERED ILLEGAL.
14. 45 DEGREE IN VALVE ONLY, NO BACK CUT ON VALVE.
15. SHIMS CAN BE USED UNDER VALVE SPRINGS WITH A LIMIT OF .060 PER SPRING.
16. MAY USE OFF SET LOCKS BUT NOT WITH SHIMS.
17. ROCKER ARMS MUST BE STOCK OR STOCK REPLACEMENT. 1.5 MAX. SELF ALIGNING ROCKERS OK
18. NO PORTING OR POLISHING.
19. NO VORTEC PARTS.
20. POLY LOCKS ALLOWED

C INTAKE

- i. STOCK CAST IRON ONLY.
- ii. NO HOLLEY PATTERN FACTORY INTAKES.
- iii. 2101 INTAKE ALLOWED
- iv. **MUST HAVE VACUUM FITTING BEHIND CARB IN THE INTAKE.**

D. CAM

- 1. **STOCK TIMING CHAIN OR CLOYES C-3023X OR CL09-1100SP ADJUSTABLE TIMING CHAIN.**
- 2. .390 - .410 LIFT.
- 3. 112 LOBE SEPARATION +/- 1 DEGREE.
- i4. ADVANCING OR RETARDING THE CAM WITH ADJUSTABLE TIMING OK.
- 5. CLOYES C-3023X ONLY - NO CAM BUTTONS.
- 6. STOCK CAM OR STOCK REPLACEMENT CAM ONLY.
- 7. DURATION FOR INTAKE + 2 DEGREES / -10 DEGREES.
- 8. .006 - 256 DEGREES.
- 9. .050 - 195 DEGREES.
- 10. .200 - 95 DEGREES.
- 11. DURATION FOR EXHAUST + 2 DEGREES / - 10 DEGREES.
- 12. .006 - 261 DEGREES.
- 13. .050 - 202 DEGREES.
- 14. .200 - 106 DEGREES.
- 15. MUST HAVE 18" VACUUM AT 1000 RPM.
- 16. HYDRAULIC CAM AND LIFTERS ONLY.
- 17. CAMS CS-274 SEALED POWER AND CCS-2 MELLING AND COMP CAM 12-105-3 ARE A STOCK PRODUCED CAM.
- 18. ALL CAMS MUST PASS THE ABOVE SPECIFICATIONS. CAMS NOT MEETING THESE SPECS WILL BE DEEMED ILLEGAL.
- 19. IT IS THE ENGINE BUILDERS\DRIVERS RESPONSIBILITY TO HAVE CAM CHECKED TO BE LEGAL\STRAIGHT BEFORE THE RACE NOT AFTER. YOU HAVE OPTIONS ON CAMS.

5.14 MISC SYSTEMS:

- 1. WET SUMP STOCK PUMP ONLY. NO EXTERNAL OIL PUMPS OR SYSTEMS (EVEN IF CONSIDERED "WET").
- 2. OIL COOLERS AND REMOTE OIL FILTERS ARE NOT PERMITTED.
- 3. NO ELECTRIC FANS
- 4. RACING PULLEYS ARE OK.

5.15

PROTEST AND CLAIM: ITEMS NOT COVERED BELOW ARE NON-PROTEST ITEMS AND WILL BE GOVERNED BY MONSTER THUNDER BOMBER SERIES AND ITS DESIGNEES.

1. SHOCK CLAIM:

a. 1 SHOCK CLAIM \$125 PER CORNER

i. CAR CLAIMING SHOCK(S) MUST FINISH IN THE TOP 5 AND ON THE LEAD LAP. CLAIMS MUST BE MADE TO TECH

OFFICIAL WITHIN 10 MINUTES AFTER THE CAR CROSSES THE SCALES

ii. SHOCK WILL BE PROVIDED AS IT COMES FROM BILSTEIN.

iii. REVERSE CLAIMS WILL BE PERMITTED.

iv. REFUSAL TO ALLOW SHOCKS TO BE CLAIMED OR CONFISCATED BY OFFICIALS WILL RESULT IN THE DRIVER LOSING ALL POINTS AND MONEY FOR THAT EVENT, AND FACE THE FOLLOWING PUNISHMENT:

1. FIRST OFFENSE – 1-WEEK SUSPENSION FROM ANY MONSTER THUNDER BOMBER SERIES SANCTIONED EVENT AND \$250 FINE

2. SECOND OFFENSE – 30-DAY SUSPENSION FROM ANY MONSTER THUNDER BOMBER SERIES SANCTIONED

EVENT AND \$500 FINE

3. THIRD OFFENSE – 365-DAY SUSPENSION FROM ANY MONSTER THUNDER BOMBER SERIES SANCTIONED

EVENT AND \$1,000 FINE

v. SERIES OR TRACK OFFICIALS MAY CONFISCATE OR CLAIM SHOCKS AT ANY TIME. IF CONFISCATED AND SHOCKS ARE DETERMINED TO BE LEGAL, THEY WILL BE RETURNED TO THE DRIVER AND POINTS AND MONEY WILL BE AWARDED AS EARNED. IF SHOCKS ARE DETERMINED TO BE ILLEGAL, THE DRIVER WILL LOSE ALL POINTS AND MONEY FROM THE EVENT AND FACE THE FOLLOWING PUNISHMENT:

1. FIRST OFFENSE – 1-WEEK SUSPENSION FROM ANY MONSTER THUNDER BOMBER SERIES SANCTIONED EVENT AND \$250 FINE

2. SECOND OFFENSE – 30-DAY SUSPENSION FROM ANY MONSTER THUNDER BOMBER SERIES SANCTIONED EVENT AND \$500 FINE

3. THIRD OFFENSE – 365-DAY SUSPENSION FROM ANY MONSTER THUNDER BOMBER SERIES SANCTIONED EVENT AND \$1,000 FINE

2. CAM PROTEST (\$300; \$100 ACCEPTANCE FEE, TRACK/SERIES RETAINS \$100. \$300 TO WINNER OF PROTEST)

a. CAM WILL BE SECURED BY TRACK/SERIES OFFICIAL AND SENT TO MONSTER THUNDER BOMBER SERIES DESIGNATED INSPECTOR TO BE INSPECTED. MULTIPLE CAM LOBES WILL BE CHECKED IN THIS PROTEST

3. TWO (2) ITEM PROTEST (\$300; \$100 ACCEPTANCE FEE, SERIES/TRACK RETAINS \$100. \$300 TO WINNER OF PROTEST)

a. MAY INCLUDE ENGINE, WHEELBASE, CHASSIS & SUSPENSION, IGNITION, CARBURETOR, REAR END, AND BRAKES. ALL OTHER ITEMS ARE GOVERNED BY MONSTER THUNDER BOMBER SERIES OFFICIALS OR PROTESTED IN ANOTHER SECTION.

4. BOTTOM END PROTEST (\$600; \$100 ACCEPTANCE FEE; \$100 TO TECH, \$600 TO PROTEST WINNER)

5. TIRE PROTEST FEE (\$125 & \$125 ACCEPTANCE FEE; \$125 TO WINNER OF PROTEST).

a. TIRES NOT CONFORMING TO THE BENCHMARK WILL RESULT IN DISQUALIFICATION, LOSS OF POINTS AND PRIZE MONEY AS

WELL AS:

- i. FIRST OFFENSE – \$500 FINE, SUSPENDED UNTIL FINE IS PAID. TRACK RETAINS \$200.
- ii. SECOND OFFENSE – \$1000 FINE, SUSPENDED UNTIL FINE IS PAID. TRACK RETAINS \$400.
- iii. THIRD OFFENSE – SUSPENSION FROM ALL MONSTER THUNDER BOMBER SERIES EVENTS AND FINE AT SERIES DISCRETION.

6. FUEL PROTEST FEE (\$150 & \$150 ACCEPTANCE FEE; \$150 TO WINNER IF PROTEST).

- a. FUEL NOT CONFORMING TO THE BENCHMARK WILL RESULT IN DISQUALIFICATION, LOSS OF POINTS AND PRIZE MONEY AS WELL

- i. FIRST OFFENSE – \$500 FINE - SUSPENDED UNTIL FINE IS PAID. TRACK RETAINS \$200.
- ii. SECOND OFFENSE – \$1000 FINE - SUSPENDED UNTIL FINE IS PAID. TRACK RETAINS \$400.
- iii. THIRD OFFENSE – SUSPENSION FROM ALL MONSTER THUNDER BOMBER SERIES EVENTS AND FINE AT SERIES DISCRETION.

7. PROTEST PROCESS

- a. ONLY DRIVER/CAR OWNER MAY PROTEST. PROTESTING CAR MUST COMPETE IN RACE IN QUESTION TO FILE PROTEST. ALL PROTESTS MUST BE PRESENTED IN WRITING, ACCCOMPANIED BY PROTEST FEE, TO THE TECH MAN WITHIN 5 MINS. OF THE WINNER OF THE FEATURE RACE CROSSING THE SCALES. PROTESTS DONE IN AN UNSPORTSMANLIKE MANNER WILL NOT BE CONSIDERED.

- b. PROTESTED CARS HAVE 5 MINS. TO ACCEPT OR REFUSE PROTEST. AFTER ACCEPTANCE, PROTESTED CAR HAS 5 MINS. TO BACK PULL PROTESTING CAR ONLY, ON EQUAL OR LESS ITEMS.

- c. TO PROTEST ANY CAR IN THE FIELD, YOU MUST FINISH DIRECTLY BEHIND THEM OR PROTEST ALL CARS BETWEEN. MUST BE ON LEAD LAP AT THE CHECKERED FLAG.

- d. AFTER PROTEST HAS BEEN FILED AND MONEY HAS BEEN PUT UP, IT WILL NOT BE RETURNED FOR ANY REASON. PROTEST CANNOT BE TAKEN DOWN ONCE IT IS FILED; THIS IS TO AVOID SWAPPING MONEY, WHICH IS UNFAIR TO THE REST OF THE FIELD.

- e. PARTS MUST BE READY FOR INSPECTION WITHIN ONE (1) HOUR. (TECH MAN DISCRETION)

- f. FOR PROTEST MONEY TO GO TO THE CAR THAT HAS BEEN PROTESTED, HE/SHE MUST TEAR DOWN AND BE CHECKED AND FOUND LEGAL. CARS FOUND ILLEGAL WILL FORFEIT POINTS AND MONEY EARNED FOR ENTIRE RACE NIGHT.

- g. QUESTIONS ON PROTEST PROCESS WILL BE MADE BY DRIVER/CAR OWNER ONLY.

- h. ONE CREW MEMBER FROM PROTESTING TEAM IS ALL THAT WILL BE ALLOWED IN TECH AREA OTHER THAN SECURITY AND TECH OFFICIALS FOR THE DURATION OF TECH PROCESS. NO SWITCHING OUT OF PROTESTING CREW MEMBER MID-TECH. NO PHONES OR CAMERAS ALLOWED IN TECH AREA WITH PROTESTING CREW MEMBER. IF CAUGHT ATTEMPTING TO TAKE PHOTOS, PROTESTING TEAM WILL BE DQ'ED. ALL PEOPLE IN TECH AREA SHALL REMAIN CALM & SPORTSMANLIKE DURING TECH PROCESS. NO DRINKING IN TECH SHED.

- i. THE TECH MAN HAS FINAL WORD ON ANY RULE OR PROTEST.

8. ILLEGAL PARTS POLICY

- a. ANY COMPETITOR CAUGHT CHEATING “WITHIN THE BOLTS” WILL BE SUBJECT TO THE FOLLOWING PENALTIES:

- i. FIRST OFFENSE - LOSS OF POINTS, MONEY AND ANY AWARDS. WRITTEN WARNING AND PROBATION FOR THE REMAINDER OF THE YEAR.

- ii. SECOND OFFENSE- LOSS OF POINTS, MONEY AND AWARDS. \$500 FINE AND 14 DAY SUSPENSION FROM MONSTER THUNDER BOMBER SANCTIONED EVENT.

- iii. THIRD OFFENSE- LOSS OF POINTS, MONEY AND AWARDS. \$1000 FINE AND 30-DAY SUSPENSION FROM MONSTER THUNDER BOMBER SANCTIONED EVENT
- iv. FOURTH OFFENSE - LOSS OF POINTS, MONEY AND AWARDS. TERMINATION OF MEMBERSHIP, INDEFINITE SUSPENSION AND FINE AT MONSTER DISCRETION.

5.16 ELECTRONIC DEVICES:

- 1. NO DATA ACQUISITIONING DEVICES (OIL, WATER, FUEL GUAGES AND TACH ALLOWED)
- 2. NO TRACTION CONTROL OR LIKE DEVICES (EXAMPLE TIRE TEMP DEVICES OR ANYTHING LIKE)
 - a. DISTRIBUTORS WILL BE CHECKED AND MAY BE IMPOUNDED AT ANY TIME.
- 3. CAMERAS MUST BE MOUNTED ABOVE THE DECK AT ALL TIMES AND CLEAR OF DRIVERS VIEW