



*Tarpaulin Systems Inc.*

## INSTRUCTIONS FOR COMPLETION OF SLIDE 'N GO® ORDER FORM

We have tried to make ordering our systems as easy as possible. The information requested is necessary in order to properly fill your order. Inaccurate or incomplete information can result in a system that does not perform properly or may not work at all.

A little extra time spent now on providing the correct information will save a lot of time later trying to correct the problem. If you have any questions as to how to complete the form or how to take measurements, please do not hesitate to call us at (800) 272-6276. Your completed order should be faxed to us toll free at (877) 333-2100.

Slide 'N Go® systems are manufactured in 5 different widths and will be provided as follows:

### Anti-Pollution / Semi-Waterproof

Outside to Outside Width of Trailer or Body	System Width Recommended (cable center to cable center)
87 ½" To 92"	93 ½" System
92+" To 95"	97" System
95+" To 98"	99" System
98+" To 102"	103" System
102+" To High Liftgate	105" System

**If you know which system width you want, or if you want one different from this chart, please indicate your preference in the SPECIAL INSTRUCTIONS section on the reverse side of this form.**

### HOW TO MEASURE

1. Make sure that all measurements are taken at the top of the trailer - not at the bottom.
2. Be especially accurate when measuring the inside and outside widths.
3. For the length - measure from the point where you are going to attach the tarp to the front of the trailer/body to the furthest rear point, which the last bow can slide to without hitting any obstacles or restrictions such as hinges and/or the rear bracket mount location.

#### **\* Important Note \***

**The Slide 'N Go® system can be installed on sloped bodies but at no time can the system be installed with a bend in it.  
It must always travel on a straight plane.**