biofit.com | 800.597.0246

Traxx (TX) Series

advantage: durability | use: laboratory, cleanroom, static control/ESD, healthcare, industrial, education

Highlighted by an 14-gauge steel seat, stools in this series are designed to handle tough industrial settings yet can be configured for use in cleanrooms.



BIOFIT°



 23" diameter tubular steel (S style) base with 21" diameter affixed footring.



 25.6" diameter, highprofile cast aluminum (A style) base.



 25.6" diameter, high-profile reinforced composite (R style) base.



 28.7" diameter, highprofile wide aluminum (W style) base.

biofit.com | 800.597.0246

Traxx Series Standard Comp			
13" dia., 14-gauge steel, soft touch			
Models with tubular steel bas	se		
Model#	Seat-Hgt.	Compatibility	
TXS-L-RC-S-XF-XA-06	Low, 15.5"-19.5"	Desk	
TXS-M-RC-S-XF-XA-06	Medium, 18"-25"	Standard Bench	
TXS-H-RC-S-XF-XA-06	High, 22"-29"	High Bench	
Models with cast aluminum b	pase		
Model#	Seat-Hgt.	Compatibility	
TXA-L-RC-S-XF-XA-06	Low, 14"-19"	Desk	
TXA-M-RC-S-XF-XA-06	Medium, 16"-23"	Standard Bench	
TXA-H-RC-S-XF-XA-06	High, 19.5"-29"	High Bench	
Models with reinforced comp	osite base		
Model#	Seat-Hgt.	Compatibility	
TXR-L-RC-S-XF-XA-06	Low, 14"-19"	Desk	
TXR-M-RC-S-XF-XA-06	Medium, 15.5"-22.5"	Standard Bench	
TXR-H-RC-S-XF-XA-06	High, 19"-28.5"	High Bench	
Models with wide aluminum I	base		
Model#	Seat-Hgt.	Compatibility	
TXW-L-RC-S-XF-XA-06	Low, 13.5"-18.5"	Desk	
TXW-M-RC-S-XF-XA-06	Medium, 15.5"-22.5"	Standard Bench	
TXW-H-RC-S-XF-XA-06	High, 19"-28.5"	High Bench	
1XW-H-RC-S-XF-XA-06	rigii, 19 -20.5	riigii belicii	

Ask about special and custom orders.

Component	MFG Code	e Description	
Footring	AFP	Adjustable height, 22" diameter, oval tube construction on solid polished cast aluminum spoke (recommended for medium and high height models with A, W or R bases, adjusts easily without knobs or levers; not available with low height models or units with S style base)	
	ATF	Adjustable height, 20" diameter, cast aluminum (recommended for medium and high height models with A, W or R bases. Not available with low height models or S style base units)	
Glides	HG	2" high polyamide glides	
Casters	LRO	Dual-wheel, soft tread, with weight-activated self-braking capability; resists movement when seat is occupied	
	R	Single-wheel, thermoplastic rubber, non-marring, ball-bearing construction; for hard floors including concrete	
	RC	Hooded dual-wheel, non-marring resistance casters, resist movement when seat is unoccupied – standard on most models	
	RK	Hooded dual-wheel, non-marring resistance casters for ESD applications; resist movement when seat is unoccupied (standard with ESD performance packages)	
Miscellaneous	SW	Skid wrapping; net cost per pallet	

Category	Class	MFG Code	
ESD	ESD w/A or W Base	K	
	ESD w/S Base	K	
Cleanroom	ISO 6	ISO6	
	ISO 5*	ISO5	
	ISO 4*	ISO4	
Cleanroom/ESD	ISO 6/ESD*	ISO6K	
	ISO 5/ESD*	ISO5K	
	ISO 4/ESD*	ISO4K	
Chrome-plated metal parts, chairs w/A, W, R base	_	С	
Chrome-plated metal parts, chairs w/S base	_	С	
*Not available with R style base.			

WARNING: This product can expose you to chemicals including wood dust, which is known to the State of California to cause cancer. For more information go to www.p65warnings.ca.gov.

