

CABINETS: Safety Cabinets

SAFETY CABINETS

- Constructed from 180-gauge steel with double walls on tops, sides, bottoms, and doors (double walls integrate a 1-1/2" airspace for added safety)
- Two side vents, both with 2" threaded fittings
- Fire baffle end cap
- High-gloss epoxy powder coatings inside and out



Acid/Corrosive Safety Cabinet

- Designed for the storage of up to 5 gallon containers of flammable and nonflammable acids and corrosive liquids
- Coated with blue epoxy powder coating for superior protection against chemical spills and splashes

Acid/Corrosive Safety Cabinet Models

MODEL #*	DOOR SPECS	CAPACITY	APPROVAL	WIDTH	DEPTH	HEIGHT	SHELF DEPTH	SHELVES	SHELF TRAYS	BTM TRAYS	WEIGHT
CAC30M	2 Doors	30 gal. (114L)	FM (1092mm)	43" (457mm)	18" (1118mm)	44" (375mm)	14-3/4" (375mm)	1	1	1	253 lbs. (115kg)
CAC45M	2 Doors	45 gal. (170L)	FM (1092mm)	43" (457mm)	18" (1651mm)	65" (794mm)	14-3/4" (375mm)	2	2	1	351 lbs. (159kg)
CAC60M	2 Doors	60 gal. (227L)	FM (227L)	31-1/4" (794mm)	31-1/4" (1651mm)	65" (711mm)	28" (375mm)	2	2	1	363 lbs. (165kg)

*M — Manual doors

Weight includes packaging

Paint/Ink Safety Cabinet

- Safely store printing inks and other paint products
- Cabinets finished with a high-gloss yellow epoxy

Paint/Ink Safety Cabinet Models

MODEL #	DOOR SPECS	CAPACITY	APPROVAL	WIDTH	DEPTH	HEIGHT	SHELF DEPTH	SHELVES	WEIGHT
PIC40M	2 Doors	40 gal. (151L)	FM (1092mm)	43" (457mm)	18" (1118mm)	44" (375mm)	14-3/4" (375mm)	3	272 lbs. (123kg)
PIC60M	2 Doors	60 gal. (227L)	FM (227L)	43" (1092mm)	18" (457mm)	65" (1651mm)	14-3/4" (375mm)	5	380 lbs. (172kg)

Weight includes packaging

Flammable Safety Cabinet

- Keep required flammable liquids safely near work areas
- Coated with high-gloss yellow HazMat finish
- Meets OSHA requirements, NFPA Code 30 requirements, and FM approval

Flammables Safety Cabinet Models

MODEL #*	DOOR SPECS	CAPACITY	APPROVAL	WIDTH	DEPTH	HEIGHT	SHELF DEPTH	SHELVES	WEIGHT
FLC30M	2 Doors	30 gal. (114L)	FM (1092mm)	43" (457mm)	18" (1118mm)	44" (375mm)	14-3/4" (375mm)	1	247 lbs. (112kg)
FLC30SC	2 Doors	30 gal. (114L)	FM (1092mm)	43" (457mm)	18" (1118mm)	44" (375mm)	14-3/4" (375mm)	1	257 lbs. (117kg)
FLC45M	2 Doors	45 gal. (170L)	FM (1092mm)	43" (457mm)	18" (1651mm)	65" (794mm)	14-3/4" (375mm)	2	342 lbs. (155kg)
FLC45SC	2 Doors	45 gal. (170L)	FM (1092mm)	43" (457mm)	18" (1651mm)	65" (794mm)	14-3/4" (375mm)	2	353 lbs. (160kg)
FLC60M	2 Doors	60 gal. (227L)	FM (227L)	31-1/4" (794mm)	31-1/4" (1651mm)	65" (711mm)	28" (375mm)	2	354 lbs. (161kg)
FLC60SC	2 Doors	60 gal. (227L)	FM (227L)	31-1/4" (794mm)	31-1/4" (1651mm)	65" (794mm)	28" (375mm)	2	364 lbs. (165kg)

*M — Manual doors

Weight includes packaging

Safety Cabinet Accessories

- Accessories include metal shelves, epoxy-coated metal shelves, polyethylene bottom trays, polyethylene shelf trays, and self-closing adapter kits

Safety Cabinet Accessories

MODEL #	TYPE	DESCRIPTION
CAS-XX	Epoxy-Coated Metal Shelf	Specify Capacity of 30, 45, or 60 gal. (114, 170, or 227L)*
FLS-XX	Metal Shelf	Specify Capacity of 30, 45, or 60 gal. (114, 170, or 227L)*
PIS-XX	Metal Shelf	Specify Capacity of 40 or 60 gal. (151 or 227L)*
CAPBT-XX	Poly. Bottom Tray	Specify Capacity of 30, 45, or 60 gal. (114, 170, or 227L)*
CAPST-XX	Poly. Shelf Tray	Specify Capacity of 30, 45, or 60 gal. (114, 170, or 227L)*
FLAK	Adapter Kits	All Flammable
CAAK	Adapter Kits	All Acid/Corrosive
PIAK	Adapter Kits	All Paint/Ink