



	A	B	C	D	E	F	G	H	I	J
4-1/2" High Hinge	6'8				37 ⁷ / ₁₆	67 ³ / ₈				
	6'10				38 ⁷ / ₁₆	69 ³ / ₈				
	7'0				39 ⁷ / ₁₆	71 ³ / ₈				
	7'2				40 ⁷ / ₁₆	73 ³ / ₈				
	7'4	40 ⁵ / ₁₆	48	7 ¹ / ₂	41 ⁷ / ₁₆	75 ³ / ₈		3 ³ / ₈	1 ¹ / ₄	1 ¹ / ₈
	7'6				42 ⁷ / ₁₆	77 ³ / ₈				
	7'6				30 ⁵¹ / ₆₄	54 ³ / ₃₂	77 ²⁵ / ₆₄			
	7'8				31 ²⁹ / ₆₄	55 ¹³ / ₃₂	79 ²³ / ₆₄			
	7'10				32 ¹ / ₈	56 ³ / ₄	81 ³ / ₈			
	8'0				32 ⁵¹ / ₆₄	58 ³ / ₃₂	83 ²⁵ / ₆₄			
5" High Hinge	6'8				37 ³ / ₁₆	67 ¹ / ₈				
	6'10				38 ³ / ₁₆	69 ¹ / ₈				
	7'0				39 ³ / ₁₆	71 ¹ / ₈				
	7'2				40 ³ / ₁₆	73 ¹ / ₈				
	7'4	40 ⁵ / ₁₆	48	7 ¹ / ₄	41 ³ / ₁₆	75 ¹ / ₈		3 ³ / ₈	1 ¹ / ₄	1 ¹ / ₈
	7'6				42 ³ / ₁₆	77 ¹ / ₈				
	7'6				30 ³⁵ / ₆₄	53 ²⁷ / ₃₂	77 ⁹ / ₆₄			
	7'8				31 ¹³ / ₆₄	55 ⁵ / ₃₂	79 ⁷ / ₆₄			
	7'10				31 ⁷ / ₈	56 ²⁷ / ₃₂	81 ⁹ / ₆₄			
	8'0				32 ³⁵ / ₆₄	57 ²⁷ / ₃₂	83 ⁹ / ₆₄			

- * All dimensions are subject to industry standard tolerances. Tolerances between hinges are non-accumulative
- * Dimensions D, E, F and G are shown from top of frame rebate to top of each hinge
- * Dimensions B, C are shown from the bottom of the jamb to the center line of the preparation.
- * Dimension C option: 46-5/16"

High Frequency Hinge Reinforcing

Drawing No. F10

Date: 07/17/2019

STANDARD HARDWARE LOCATIONS (FRAME)

Drawn by: LX

PROJECT:

DAYBAR

SHEET:

○ OF ○