



# SAFETY DATA SHEET

## SECTION I. PRODUCT IDENTIFICATION

Product name: Kaolin Clay  
 Product ID: 24010, 32710  
 Relevant Identified Uses: Various commercial and industrial uses

Company: Buff City Soap  
 Company Address: 2716 Fairmount St, Dallas, TX 75201 USA  
 Company Phone: +1 (844) 468-7627

Emergency Contact: +1 (844) 468-7627

## SECTION II. HAZARD(S) IDENTIFICATION

### GHS/Hazcom 2012 Classification

Physical:	Health:	Environmental:
Not Hazardous	Carcinogen Category 1A Specific Target Organ/Toxicity (Repeated Exposure) Category 1	Not Hazardous

### GHD/Hazcom 2012 Label:



Danger

### Statement of Hazard

May cause cancer by inhalation. Cause damage to lungs through prolonged or repeated exposure by inhalation

### Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not eat, drink or smoke when using this product. Wear protective gloves and safety glasses or goggles. In case of inadequate ventilation wear respiratory protection

### Response

If exposed or concerned: Get medical attention

### Disposal

Dispose of in accordance with local, state & federal regulations.

Hazards not otherwise  
classified (HNOC)

None know

### SECTION III. COMPOSITION/INFORMATION ON INGREDIENTS

CAS #	Component	Percentage
1332-58-7	Kaolin (Aluminum Silicate)	> 95%
14808-60-7	Crystalline Silica in the form of Quartz	< 3%
13463-67-7	Titanium Dioxide	< 2%
12001-26-2	Mica (Muscovite)	< 2%
14464-46-1	Crystalline Silica in the form of Cristobalite	< 1.5%

### SECTION IV. FIRST-AID MEASURES

**Gross Inhalation:** Remove victim to fresh air. If breathing has stopped, perform artificial respiration. If breathing is difficult have qualified personnel administer oxygen. Get prompt medical attention.

**Skin Contact:** No first aid should be needed since dermal contact with this product does not affect the skin. Wash exposed skin with soap and water before breaks and at the end of the shift.

**Eye Contact:** Flush the eyes immediately with large amounts of running water, lifting the upper and lower lids occasionally. If irritation persists or for imbedded foreign body, get immediate medical attention.

**Ingestion:** If large amounts are swallowed, get immediate medical attention.

**Most Important Symptoms and Effects, Both Acute and Delayed:** May cause eye irritation with redness and tearing. Exposure to dust may cause mucous membrane and respiratory irritation, cough, sore throat, nasal congestion, sneezing and shortness of breath. However, there may be no immediate signs or symptoms of exposure to hazardous concentrations of respirable crystalline silica (quartz).

**Indication of immediate medical attention and Special Treatment Needed:** None required.

### SECTION V. FIRE-FIGHTING MEASURES

**Suitable Extinguishing Media:** This product will not burn but is compatible with all extinguishing media. Use fire-extinguishing media appropriate for surrounding materials

**Specific Hazards Arising from the Chemical:**

**Unusual Fire and Explosion Hazards:** Not flammable or combustible. Dry powders may accumulate static charge in handling which can be a source of ignition for flammable atmosphere.

**Hazardous Combustion Products:** None

**Special Protective Equipment and Precautions for Fire-Fighting:** None required with respect to his product. Firefighters should always wear self-contained breathing apparatus for fires indoors or in confined spaces.

## **SECTION VI. ACCIDENTAL RELEASE MEASURES**

**Personal Precautions, Protective Equipment and Emergency Procedures:** Wear appropriate protective equipment.

**Environmental Precautions:** Report spills and releases as required to appropriate authorities.

**Methods and Material for Containment/Cleanup:** If uncontaminated, collect using method (HEPA vacuum or wet method) and place in appropriate container for use. If contaminated: a) use appropriate method for the nature of contamination, and b) consider possible toxic or fire hazards associated with the contaminating substances. Collect for appropriate disposal.

## **SECTION VII. HANDLING AND STORAGE**

**Precautions for Safe Handling:** Do not breathe dust. Do not rely on your sight to determine if dust is in the air. Silica may be in the air without a visible dust cloud. Use normal precautions against bag breakage or spills of bulk material. Avoid creation of respirable dust. Use good housekeeping in storage and use areas to prevent accumulation of dust in work areas.

To reduce the risk of developing silicosis, lung cancer and other adverse health effects, the ACGIH recommends that the industrial hygienist use every means available to keep exposures below the recommended TLV. NIOSH recommends reducing airborne exposure levels as low as possible below NIOSH's recommended exposure limit, substituting less hazardous materials when feasible, using appropriate respiratory protection when source controls cannot keep exposures below the recommended limit and making medical examinations available to exposed workers.

Use adequate ventilation and dust collection. To minimize exposure, wear a respirator approved for silica dust when using, handling, storing or disposing of this product or bag. Refer to the most recent government and local regulations when selecting a respirator. Maintain, clean and fit test respirators in accordance with the most recent government and local regulations. Maintain and test ventilation and dust collection equipment. Launder clothing that has become dusty. Empty containers (bags, bulk containers, storage tanks, etc.) retain silica residue and must be handled in accordance with the provisions of this Material Safety Data Sheet. WARN and TRAIN employees in accordance with state and federal regulations.

**WARN YOUR EMPLOYEES (AND YOUR CUSTOMERS AND USERS IN CASE OF RESALE) BY POSTING, AND OTHER MEANS, OF THE HAZARDS AND OSHA AND ANY OTHER APPLICABLE REGULATORY PRECAUTIONS TO BE USED. PROVIDE TRAINING FOR YOUR EMPLOYEES ABOUT OSHA PRECAUTIONS.**

Dust can accumulate electrostatic charges due to friction from transfer and mixing operations and cause an electrical spark (ignition source) which can ignite flammable liquids and atmospheres. Provide adequate precautions when adding this product to flammable and combustible mixtures like

paints and coating, such as electrical grounding and bonding, inert atmosphere or non-sparking tools. However, bonding and grounds may not eliminate the hazard for static accumulation.

See also American Society for Testing and Materials (ASTM) Standard Practices E1132-99a, “Standard for Health Requirements Relating to Occupational Exposure to Respirable Crystalline Silica”.

**Conditions for Safe Storage, Including any Incompatibilities:** Store in a dry location.

## SECTION VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Exposure Guidelines:

Definitions:

MSHA means Mine Safety and Health Administration

NIOSH means National Institute for Occupational Safety and Health

OSHA means Occupational Safety and Health Administration

PEL means OSHA Permissible Exposure Limit

REL means NIOSH Recommended Exposure Limit

TLV means American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value

TWA means time-weighted average.

Component	OSHA PEL	ACGIH TLV	NIOSH REL	MSHA
Crystalline Silica, quartz	0.05 mg/m <sup>3</sup> TWA (respirable dust)*	0.025 mg/m <sup>3</sup> TWA (respirable dust)	0.05 mg/m <sup>3</sup> TWA (respirable dust)	<u>10 mg/m<sup>3</sup></u> % Silica +2 (Respirable measured as an 8-hour TWA)
Cristobalite	<u>1 x 10 mg/m<sup>3</sup></u> 2% Silica + 2 (Respirable measured as an 8-hour TWA)	0.025 mg/ m <sup>3</sup> 8-hour TWA (respirable fraction)	0.05 mg/ m <sup>3</sup> TWA (respirable dust)	<u>1 x 10 mg/m<sup>3</sup></u> 2% Silica + 2 (respirable measured as an 8-hour TWA)
Kaolin	5 mg/ m <sup>3</sup> TWA (respirable fraction) 15 mg/m <sup>3</sup> TWA (total dust)	2 mg/m <sup>3</sup> m <sup>3</sup> TWA (respirable fraction)	5 mg/m <sup>3</sup> m <sup>3</sup> TWA (respirable fraction) 10 mg/m <sup>3</sup> TWA (total dust)	10 mg/ m <sup>3</sup> TWA (total dust)
Mica	20 mppcfa TWA (respirable fraction)	3 mg/ m <sup>3</sup> TWA (respirable fraction)	3 mg/ m <sup>3</sup> TWA (containing <1% Quartz)	20 mppcfa TWA (respirable fraction)
Titanium Dioxide	PEL – 15 mg/ m <sup>3</sup> TWA (total dust)	10 mg/ m <sup>3</sup> TWA	None established	15 mg/ m <sup>3</sup> TWA (total dust)

\*2016 OSHA PEL effective as follows:

Construction June 23, 2017 29CFR 1926.1153

General Industry and Maritime June 23, 2018 29CFR 1910.1053 / 1915.1053

Oil and Gas including Hydraulic Fracturing June 23, 2018 29CFR 1910/1053

The OSHA PEL for Quartz until the effective dates for new PEL above:

10 mg/3 TWA (respirable dust)  
%SiO<sub>2</sub>+2

30 mg/m<sup>3</sup> TWA (total dust)  
%SiO<sub>2</sub>+2

Crystalline silica exists in several forms, the most common of which are quartz (i.e., this product), trydimite and cristobalite, with quartz being the most common form found in nature. If quartz is heated to more than 870<sup>0</sup> C, it can change form too trydimite and if quartz is heated t more than 1450<sup>0</sup> C, it can change form to cristobalite.

**Appropriate engineering controls:** Use local exhaust as required to maintain exposures as far as possible below applicable occupational exposure limits. See Also ACGIH “Industrial Ventilation – A Manual for Recommended Practice” (current edition). Control of exposure to dust must be accomplished as far as feasible by accepted engineering control measures (for example, enclosure or confinement of the operation, general or local exhaust ventilation and substitution of less toxic materials). Refer to the OSHA Respirable Crystalline Silica standards, 29CFR1910.1053, 1915,1053 and 1926.1053 for specific requirements for engineering controls.

**Personal Protection Equipment:**

**Respiratory Protection:** When effective engineering controls are not feasible, or while they are being implemented, appropriate respiratory protection must be used. Use appropriate respirable particulates based on consideration of airborne workplace concentrations and duration of exposure arising from intended end use. Refer to the OSHA Respirable Crystalline Silica standards, 29CFR1910.1053, 1915,1053 and 1926.1053 for specific requirements for respiratory protection. Always refer to the most recent government and local standards.

**Gloves:** Protective gloves recommended

**Eye Protection:** Safety glasses or goggles recommended.

**Other Protective Equipment/Clothing:** As appropriate for the work environment. Dusty clothes should be laundered before reuse.

**SECTION IX. PHYSICAL AND CHEMICAL PROPERTIES**

Form:	Solid	Appearance:	White/Cream colored powder
Viscosity:	Not applicable	Odor	Earthy odor
pH:	Not applicable	Odor Threshold:	Not applicable
Boiling Point/Range:	Not applicable	Vapor Density:	Not applicable
Melting point/freezing point:	Not applicable	Evaporation Rate:	Not applicable
Flammability (solid, gas):	Fully oxidized, will not burn	Partition coefficient (n-octanol/water):	Not applicable
Decomposition temperature:	Not applicable	Vapor Pressure:	Not applicable
Flash Point:	Non-combustible inorganic material	Relative density:	2.58
Lower Explosion Limit:	Not applicable	Solubilities:	Negligible in water
Upper Explosion Limit:	Not applicable	Autoignition Temperature:	Will not burn

## SECTION X. STABILITY AND REACTIVITY

**Reactivity:** This product is not reactive under normal conditions of storage and use.

**Chemical Stability:** This product is stable at normal temperatures.

**Possibility of Hazardous Reactions:** None known

**Conditions to Avoid:** When exposed to high temperatures, free quartz can change crystal structures to form tridymite (above 870<sup>0</sup> C) or cristobalite (above 1470<sup>0</sup> C) which have greater health hazards than quartz.

**Incompatible Materials:** Powerful oxidizing agents such as fluorine, chlorine, trifluoride, manganese trioxide, etc.

**Hazardous Decomposition Products:** Silica will dissolve in hydrofluoric acid producing a corrosive gas, silicon tetrafluoride.

## SECTION XI. TOXICOLOGICAL INFORMATION

### Information on Toxicological Effects

#### Potential Health Effects:

**Inhalation:** Breathing silica dust may not cause noticeable injury or illness even though permanent lung damage may be occurring. Inhalation of dust may have serious chronic effects (see below Repeat dose Toxicity).

**Skin Contact:** No adverse effects expected.

**Eye Contact:** Contact may cause mechanical irritation and possible injury.

**Ingestion:** No adverse effects expected for normal, incidental ingestion.

**Chronic Health Effects:** See Repeat Dose Toxicity below with respect to silicosis, cancer status and other data with possible relevance to human health.

**Signs and Symptoms of Exposure:** Exposure to dust may cause mucous membrane and respiratory irritation, cough, sore throat, nasal congestion, sneezing and shortness of breath. However, there may be no immediate signs or symptoms of exposure to hazardous concentrations of respirable crystalline silica (quartz). See Repeat Dose Toxicity below for symptoms of silicosis. The absence of symptoms is not necessarily indicative of safe conditions.

**Acute Toxicity Values:** Silica: LD50 oral rat >22,500 mg/kg.  
Titanium Dioxide: LD oral rat >12,000 mg/kg.

**Skin Sensitization:** Not a skin sensitizer in animals or humans.

## **Repeated Dose Toxicity:**

- Silicosis:** Excessive inhalation of respirable crystalline silica dust may cause a progressive, disabling and sometimes fatal lung disease called silicosis. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with silicosis are predisposed to develop mycobacterial infections (tuberculous and non-tuberculous) and fungal infections. Inhalation of air with a very high concentration of respirable silica dust can cause the most serious forms of silicosis in a matter of months or a few years. Some epidemiological studies have concluded that there is significant risk of developing silicosis even at airborne exposure levels that are equal to the recommended NIOSH REL, and ACGIH TLV.
- Pneumoconiosis:** Excessive inhalation of respirable kaolin dust or mica dust may cause pneumoconiosis, a respiratory disease, which can result in delayed, progressive, disabling and sometimes fatal lung injury. Symptoms include cough, shortness of breath, wheezing, non-specific chest illness and reduced pulmonary function. This disease is exacerbated by smoking. Individuals with pneumoconiosis are predisposed to develop tuberculous.

## **Other Data with Possible Relevance to Human Health:**

There is some evidence that breathing respirable crystalline silica or the disease silicosis is associated with an increased incidence of significant disease endpoint such as scleroderma (an immune system disorder manifested by fibrosis of the lungs, skin and other internal organs) rheumatoid arthritis, systemic lupus, erythematosus, sarcoidosis, chronic bronchitis, chronic obstructive pulmonary disease (COPD), emphysema, chronic kidney disease and end-stage renal disease.

**Carcinogenicity:** The International Agency for Research on Cancer has determined that crystalline silica is carcinogenic to humans (Group 1 – carcinogenic to humans). Refer to IARC Monograph 100C, A Review of Human Carcinogens: Arsenic, Fibres, and Dusts (published in 2011) in conjunction with the use of these materials. The National Toxicology Program classifies respirable crystalline silica as “known to be a human carcinogen”. Refer to Twelfth Report on Carcinogens (2011). The American Conference of Governmental Industrial Hygienists (ACGIH) classifies crystalline silica, quartz, as a suspected human carcinogen (A2). NIOSH classifies titanium dioxide as a potential occupational carcinogen. IARC has classified titanium dioxide as possibly carcinogenic to humans (Group 2B). Refer to IARC Monograph 93, Carbon Black, Titanium Dioxide and non-Asbestiform Talc (published in 2006).

**Developmental/Reproductive Toxicity:** No specific data is available, however, there is no evidence that silica exposure has any effect on reproduction.

**Genetic Toxicity:** No specific data is available, however, there is no evidence that silica is a germ cell mutagen.

## **SECTION XII. ECOLOGICAL INFORMATION**

**Toxicity:** Practically non-toxic to aquatic organisms. Silica: LC50 carp >10,000 mg/L/72 hr.

**Persistence and Degradability:** Silica is not degradable.

**Bioaccumulative Potential:** Not expected to bioaccumulate.

**Mobility in Soil:** Not applicable.

**Results of PBT and VPvB Assessment:** None required.

**Other Adverse Effects:** None known.

## **SECTION XIII. DISPOSAL CONSIDERATIONS**

### **Water Treatment Methods:**

If uncontaminated, dispose as an inert, non-metallic mineral. If contaminated, dispose in accordance with all applicable local, state/provincial and national/federal regulations in light of the contamination present. It is the responsibility of the waste generator to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

## **SECTION XIV. TRANSPORT INFORMATION**

Not regulated for transportation under IATA/ICAO, IMDG, US DOT, EU ADR, or Canadian TDG Regulations. Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC Code: None.

## **SECTION XV. REGULATORY INFORMATION**

**SARA 311/312:** Hazard Categories for SARA Section 311/312 Reporting: Chronic Health

**SARA 313:** This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements under the SARA Section 313 (40 CFR 372): None

**CERCLA Section 103 Reporting Quantity:** None

**California Proposition 65:** This product contains crystalline silica (respirable) and titanium dioxide which are known to the State of California to cause cancer.

**Toxic Substances Control Act:** All of the components of this product are listed on the EPA TC Inventory or exempt from premanufacture notification requirements.



**European Inventory of Commercial Chemical Solutions:** All the components of this product are listed on the EINECS inventory or exempt from notification requirements.

**EU REACH Status:** This substance is except from REACH registration.

**Canadian Environmental Protection Act:** All the components of this product are listed on the Canadian Domestic Substances List or exempt from notification requirements.

**Canadian WHMIS Classification:** Class D, Division 2, Subdivision A (Very Toxic Material causing other Toxic Effects)

This SDS has been prepared according to the criteria of the Controlled Products Regulation (CPR) and the SDS contains all of the information required by the CPR.

**Japan METI:** All of the components of this product are existing chemical substances as defined in the Chemical Substance Control Law.

**Australian Inventory of Chemical Substances:** All of the components of this product are listed on the AICS inventory or exempt from notification requirements.

**Australian National Occupational Health & Safety Commission Status:** Hazardous according to the criteria of Australian National Occupational Health & Safety Commission – Harmful (Xn) R48/20 Harmful: Danger of serious damage to health by prolonged exposure by inhalation.

**Korea:** All of the components of this product are listed on the ECL inventory or exempt from notification requirements.

**Philippines:** All of the components of this product are listed on the PICCS inventory or exempt from notification requirements.

**New Zealand:** All of the components of this product are listed on the HSNO inventory or exempt from notification requirements.

**China:** All of the components of this product are listed on the IECSC inventory or exempt from notification requirements.

**Taiwan:** All of the components of this product are listed on the CSNN inventory or exempt from notification requirements.

## **SECTION XVI. OTHER INFORMATION**

NFPA Hazard Rating: Health: 1 Fire: 0 Reactivity: 0

HMIS Hazard Rating: Health: \* Fire: 0 Reactivity: 0

\*Warning – Chronic health effect possible – inhalation of silica dust may cause lung injury/disease (silicosis). Take appropriate measures to avoid breathing dust. See Section III.

**SDS Date of Preparation/Revision:** March 2017

**Revision Summary:** Section VII Precautions for Safe Handling; Section VIII Exposure Guidelines, Appropriate Engineering Controls, Respiratory Protection

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

This information has been obtained from current and reliable sources. Individuals using this information must do their independent judgment in determining its appropriateness for a particular use/purpose. User should perform all tests and analysis necessary to assure that its finished parts incorporating material or products will be safe and suitable for use under end-use conditions. The user of the product is solely responsible for compliance with all laws and regulations applying to the use of the products, including intellectual property rights of third parties.