IMMEDIATE ZONE CHECKLIST

Materials		
	1. Crawl spaces: Remove combustible material and install 1/8" mesh screening on vents.	
	2. Decks and elevated porches: Line ground with gravel and place 1/8" mesh screening between low-profile decks from surface to ground to block embers. Remove debris, leave and needles from deck surfaces.	
	3. Eaves, Soffits and Vents: Reduce the size and number of embers that pass through Cover vents and eaves by covering them with a 1/8" metal mesh screening. Use closure device for foundation vents and installing a louver-type dryer vent that stays closed unless the dryer is running.	
	4. Gutters: Keep gutters clean of all material.	
	5. Roof: Keep roofs clear of leaf litter and pine needles.	
	6. Windows: Consider double-paned windows or shutters over single-paned windows to mitigate radiant heat.	
Lar	ndscaping / Hardscaping	
	7. Dead Vegetation, dried leaves, pine needles and ground debris should be removed.	
	8. Consider installing hardscaping around the perimeter of the home — keep free of ground/litter debris.	
	9. Remove trees and shrubs from the area, especially Juniper, and/or replace with succulents.	
	10. Trim trees that overhang into this area.	
	11. Avoid wood mulch — use compost or leave bare dirt.	
	12. Esnure yuou have at least 6" of non-ignightable material before your siding.	

INTERMEDIATE ZONE CHECKLIST

Landscaping/Hardscaping		
	1. Mow vegetation around propane tanks.	
	2. Create fuel breaks with walkways, patios and decks.	
	3. Keep lawns and native grasses mowed to a height of four inches.	
	4. Remove ladder fuels (vegetation under trees) so a surface fire cannot reach the crowns.	
	5. Tree placement should be planned to ensure that the mature canopy is at least 10 feet from the structure.	
	6. Water trees, plants and lawns to keep them from becoming dry.	

EXTENDED ZONE CHECKLIST

Landscaping		
	1. Dispose of heavy accumulations of ground litter/debris.	
	2. Remove dead plant and tree material.	
	3. Remove small conifers growing between mature trees.	
	4. Remove vegetation adjacent to storage sheds or other outbuildings within this area.	
	5. Clear alleyways of vegetation, overhanging trees and ground debris.	
	6. Trees 30 to 60 feet from the home should have at least 12 feet between canopy tops.	