

# TECHNICAL SPECIFICATIONS – GREASEAWAY GA18-22



## TECHNICAL SPECIFICATION GREASEAWAY GA18-22

### APPLICATIONS

- Dishwashers
- Single or multi sink
- Combi ovens

### FLOW RATES & CERTIFICATION

- CE / UKCA Certified
- In accordance with BSEN1825
- 1.60 liters per second

### OPTIONS

- Wheel risers for high stack pipes
- Low level wheels for height restrictions
- 40mm or 50mm inlet &

### Plumbing Connections

Inlet: 40mm or 50mm  
Outlet: 40mm or 50mm

### Electrical Rating

Voltage: 230V  
Frequency: 50Hz  
Current: 2.3A

### Operation Times

Set by user  
One cycle every 24 hours  
7 Days a week

### Average Power Consumption

52.8W per hour

### STANDARD FEATURES & FUNCTIONS


- Modular detachable design for simplified servicing and maintenance
- Automatic FOG (Fats, Oils & Grease) removal system
- Digitally controlled operation with integrated thermostat for consistent performance
- Integrated mobility system with handles and adjustable wheels for ease of installation
- Isolation slide valves for safe and controlled operation
- Separated electrical and mechanical components for enhanced safety and reliability
- Reduces manual grease handling and site downtime
- Designed for commercial kitchens requiring reliable grease management



No Fuss Maintenance & Repairs



Smart Product Features



Water Authority Compliant

# TECHNICAL SPECIFICATIONS – GREASEAWAY GA18-22

## DIMENSIONS:

