

MORGAN PRODUCTS

PNEUMATIC CHEMICAL PUMPS FOR THE GAS AND OIL INDUSTRIES

Pneumatic Diaphragm Injectors

Model (No Timer)	Diaphragm Displacement	Pump Ratio	Diaphragm Size in - cm.	Connections All NPT Input/Output	Maximum Discharge PSI - BAR	Output Per Hour Gal. / Lts.
D10-316	.8 cc	1:1	1 - 2.5	1/4 -M / 1/4-M	125 - 8.6	.06 - .63 / .24 - 2.4
D10-PVC	.8 cc	1:1	1 - 2.5	1/4 -M / 1/4-F	125 - 8.6	.06 - .63 / .24 - 2.4
D15-316	6.6 cc	1:1	1.5 / 3.8	1/4 -M / 1/4-M	125 - 8.6	.5 - 5.2 / 2 - 20
D15-PVC	6.6 cc	1:1	1.5 / 3.8	1/4 -M / 1/4-F	125 - 8.6	.5 - 5.2 / 2 - 20
D25-316	21.2 cc	1:1	2.5 / 6.4	1/2 -M / 1/2-M	125 - 8.6	2 - 17 / 6.3 - 63
D25-PVC	21.2 cc	1:1	2.5 / 6.4	1/2 -M / 1/2-F	125 - 8.6	2 - 17 / 6.3 - 63
D40-316	51.0 cc	1:1	4 / 10	3/4 -M / 3/4-M	125 - 8.6	3 - 30 / 11 - 114
D40-PVC	51.0 cc	1:1	4 / 10	3/4 -M / 3/4-F	125 - 8.6	3 - 30 / 11 - 114

Notes:

All pumps require TR1 timing relay, TR2 timing relay or electric solenoid valve.

All pumps are shipped with mounting stand.

Maximum stroke rate for all pumps is 50 SPM.

MORGAN PRODUCTS INC. 28103 Ave. Stanford / Valencia, CA 91355

(661) 257-3022 - (800) 421-8910 - FAX (661) 257-3385

E-Mail info@morganproducts.com - Web www.morganproducts.com