SPECIFICATION SHEET



customer :	natio		date:
phone :	addr	ess:	
fax :	signa	ature of custon	ner:
e-mail :	requ	ested date of d	elivery:
type of boat:	mould no.:	rigging:	
crew weight (averag		normal: pt stb	italien: italien: or: stb pt stb stroke: stroke: stroke:
rigger scull:		\bigcirc	\circ \circ \circ
rigger sweep:		bow	bow bow bow
coxswain: □	sitting in stern (four, eight) lying in bow (pair, four)		
section: yes / no	(seat no. 6 / 7)		
length of tracks:	standard = 83cm		
(track without stoppers)	other length:	sketch for out	rigger dimensions:
sliding seat		(1)	pin Spread:
\Box carbon with	standard height	$\langle \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \$	b) middle of boat-pin
oval recesses	☐ medium (5mm lower)		
	\square low (10mm lower)	\setminus (\bigcirc)	Height:
□ carbon with big	☐ high (5mm higher)		 a) deepest point of seat (1) to base of oarlock (2)
holes	\square extra high (10mm higher)		(2)
noies			
Energy in a set	height adjustable		
gates: Emp. insert	gates:		
	other:		
outrigger dimensions (s. sketch):			
oarlock set in middle po	osition	optionals:	
		round carbo	on profiles at canvas
	scull sweep		carbon fin rudder
a) height starboard		steering de	vice integrated inside canvas
(left hand):	cmcm	Textrem de	
height portside	-	Olympic Ec	lition
(right hand):	cm	Textremde	cks and carbon layer inside
			ordered with round carbon profiles at canvas)
b) spread	cmcm	└ full carbon	stretcher with 4° vertical curve
steering shoe	right foot		eplate for variable shoe angle
seat no.:	🗌 left foot		carbon with 4° \Box or 6° \Box
	seat no.:	additional v	0
shoe sizes:	1 = 5 =	remarks / spec	cial requests:
(EU sizes)	2 = 6 =		
	3 = 7 =		
	4 = 8 =		
electr. system:			
CoxBox cplt.	CoxBox GPS cplt.		
CoxBox wiring only	-		
StrokeCoach Surge			
SpeedCoach GPS2	SpeedCoach GPS2 + Tr. P.		
	r StrokeC. T-bracket A-bracket		
boat cover:	polyester, PVC coated,		
	with zip		
cover for outrigger:	qty.:		