

Faber

Steel Cylinders

Hot Dip Galvanized

HDG is the most durable, corrosion-free exterior finish possible. The HDG process involves submerging the cylinder into molten zinc. The zinc metallurgically bonds to the steel so that it won't come off.

- 3442 psi (237 bar) working pressure
- Phosphatized-cleaned interior
- DOT SP13488 and TC SU7694-237
- O2 cleaned for use with up to 40% pre-blended nitrox
- Includes self-draining tank boot with round rim
- Inlet thread is standard 3/4"-14 NPSM

VALVE OPTIONS FOR STEEL

- With XS Scuba PVD PRO Valve
- With Thermo PRO Valve
- With Thermo DIN Valve
- With Thermo Modular Valve
- With XS Scuba Modular Valve
- No Valve
- No Boot



| Part # | HP80-HDG | HP100-HDG | HP120-HDG | HP117-HDG | HP133-HDG |
|------------------|--------------------------|---------------------------|---------------------------|-------------------------|-------------------------|
| Stated Volume | 80 cu ft | 100 cu ft | 120 cu ft | 117 cu ft | 133 cu ft |
| True Capacity | 81.7 cu ft / 10.2 liters | 101.3 cu ft / 12.9 liters | 120.1 cu ft / 15.3 liters | 117.8 cu ft / 15 liters | 133.5 cu ft / 17 liters |
| Service Pressure | 3442 psi / 237 bar | 3442 psi / 237 bar | 3442 psi / 237 bar | 3442 psi / 237 bar | 3442 psi / 237 bar |
| *Buoyancy Full | - 8.05 lbs / -3.65 kg | - 8.41 lbs / -3.81 kg | - 8.82 lbs / -4.00 kg | - 9.12 lbs / -4.13 kg | - 9.08 lbs / -4.12 kg |
| *Buoyancy Empty | - 1.74 lbs / -0.79 | -0.59 lbs / -0.15 | 0.65 lbs / 0.29 | 0.35 lbs / 0.16 | 1.45 lbs / 0.66 |
| Weight Empty | 28.3 lbs / 13.0 kg | 34.0 lbs / 15.6 kg | 39.2 lbs / 17.8 kg | 37.6 lbs / 17.7 kg | 42.4 lbs / 19.4 kg |
| Outside Diameter | 7.25" / 184 mm | 7.25" / 184 mm | 7.25" / 184 mm | 8.00" / 203 mm | 8.00" / 203 mm |
| Length | 20.8" / 53.0 cm | 25.3" / 64.5 cm | 29.1" / 74.5 cm | 24.2" / 61.5 cm | 26.85" / 68.0 cm |
| REE | 68 cc | 86 cc | 100 cc | 100 cc | 113 cc |

HYDRO DATES ON NEW FABER STEEL CYLINDERS

We ship cylinders with the "freshest" possible hydro date. We are limited in some models because of high manufacturing quantities and relatively low sales volume. Please understand, that steel cylinders shipped to your location within 18 months from date of manufacture are considered "current hydro" and not subject to further discounts.

OXYGEN USE WITH FABER STEEL CYLINDERS

Faber steel cylinders are cleaned at the factory for oxygen-enriched service up to 40% pre-blended nitrox. If you intend to use this cylinder for oxygen-enriched service, it is the responsibility of the cylinder user to insure that the cylinder and all components are maintained in a proper state of oxygen cleanliness in strict accordance with regulatory requirements and industry standards.

*In Sea Water with Valve