



PACIFIC SHUNTS, LLC

Type FJ – 1500 through 6000 Amperes



FEATURES & SPECS

Current Ratings 1500-600 Amps

50mV, 100mV or custom outputs

±.25% STD Accuracy

Operating Temp: 10°C to 60°C

APPLICATIONS

Industrial Power Supplies

Inverters

UPS Systems

MATERIALS

Resistance Element: Manganin

Terminal Block: Brass

Hardware: Brass

50mV

Part Number	Current Rating	A	B	C	D	E	F	G
FJ-1500-50	1500	9.62	3.0	1.0	3.62	0.43	2.0	0.50
FJ-2000-50	2000	9.62	4.0	1.0	3.62	0.43	2.0	1.00
FJ-3000-50	3000	9.62	4.0	1.5	3.62	0.56	2.0	1.00
FJ-4000-50	4000	9.62	5.0	1.5	3.62	0.56	2.5	1.25
FJ-5000-50	5000	9.62	5.0	1.5	3.62	0.56	2.5	1.25
FJ-6000-50	6000	9.62	5.0	2.0	3.62	0.56	2.5	1.25

100mV

Part Number	Current Rating	A	B	C	D	E	F	G
FJ-1500-100	1500	11.25	3.0	1.0	5.25	0.43	2.0	0.50
FJ-2000-100	2000	11.25	4.0	1.0	5.25	0.43	2.0	1.00
FJ-3000-100	3000	11.25	4.0	1.5	5.25	0.56	2.0	1.00
FJ-4000-100	4000	11.25	5.0	1.5	5.25	0.56	2.5	1.25
FJ-5000-100	5000	11.25	5.0	1.5	5.25	0.56	2.5	1.25
FJ-6000-100	6000	11.25	5.0	2.0	5.25	0.56	2.5	1.25

