## **Guidelines for the Installation of Patio Gates**

- ♣ A professional insured contractor must do the installation.
- ♣ A drawing of the design of the gate and railing must be submitted to the Board for approval PRIOR to installation.
- → All gates and railings must be painted BLACK ONLY.
- → The gate and the railing MUST BE THE SAME HEIGHT as the patio wall.
- → The bottom of the gate and railing must be 3 6"from the ground.
- ➡ The gate and railing must be installed on the patio floor ONLY.

  A gate and/or railing are NOT allowed to extend beyond the area of the patio ground; installation of posts is <u>NEVER</u> allowed in the planters.
- ♣ If any permits are required by the City of Fullerton, it will be the owner's responsibility to obtain them.
- → All future maintenance of the patio gate and railing will be yours, or a future owner's responsibility.
- ➡ The approval is valid for a period of six (6) months. If additional time is needed to install the patio tiles, another request in writing must be submitted to the Board for approval.

➡ If there are any questions or concerns regarding any of the above, please fell free to contact

J.L. Gill Management Co., Inc. 10440 Beach Blvd. #308 Stanton, Ca. 90680 (714) 826-5549 FAX (714) 821-6382

Signature	JLGILLMANAGEMENT@GMAIL.COM
Print Name	
Unit address	
Date	
Date	