

DESCRIPTION

BIOFLEX CANOPY C is a purified, inorganic calcium chloride.

INTENDED USAGE

BIOFLEX CANOPY C is used to create an instant set cure for the Canopy liquid applied membrane.

PROPERTIES

ASTM Classification: Type S, Grade 2, Class B

AASHTO M144: Meet or Exceed

Calcium Chloride Assay: > 90%

Pellet Size Distribution -

> 4.8mm: < 20%

0.6 > 4.8mm: > 76%

< 0.6mm: < 4%

ASTM D98 Purity -

Total alkali chlorides (as NaCl): < 6%

Total Magnesium (as MgCl₂): > 0.5%

Calcium Hydroxide: > 0.2%

HANDLING

COVERAGE RATES : Mix 1 lb. to 1 gal. of water.

SHELF LIFE: Susceptible to moisture contamination. Tightly seal unused product and store in dry space.

CONTAINERS: 50 lbs. (22.7 kgs.) pail

SHIPPING: Multiple pails on standard skid.

www.bioflexroofs.com

833.425.2441

TECHSUPPORT@BIOFLEXROOFS.COM



LIMITED WARRANTY

BIOFLEX ROOF PRODUCTS warrants this product to be free of defects according to our published literature at time and place of shipment.

DISCLAIMER

The information herein contained is, to the best of our knowledge, accurate and reliable.

BIOFLEX ROOF PRODUCTS cannot, however, guarantee results in connection with the use of this information.

Specifier and User shall be responsible for determining the suitability of the products for specific applications.

BIOFLEX ROOF PRODUCTS copyright 2022

www.**BIOFLEXROOFS**.com

833.425.2441

TECHSUPPORT@BIOFLEXROOFS.COM