

DESCRIPTION

BIOFLEX FLASH N is an uncured neoprene rolled sheet which offers resistance to UV, oxidation, oils, grease, and solvents.

INTENDED USAGE

BIOFLEX FLASH N is used for flashing of drains, curbs, transitions, penetrations, and expansion joints as an accessory and is intended for exposed conditions in waterproofing and roofing applications.

PROPERTIES

Roll Dimensions	6" x 100' (152 mm x 30.5 m) 12" x 100' (305 mm x 30.5 m) 18" x 100' (457 mm x 30.5 m) 24" x 100' (457 mm x 30.5 m) 36" x 100' (457 mm x 30.5 m) 48" x 100' (457 mm x 30.5 m)
Thickness	60 Mil (1.5mm)
Weight	0.42 lbs./ft ² (2 kgs./m ²)
Tensile Strength	1484 psi (10.2 MPa)
Elongation	325%
Tear Resistance	171 lbs/in. (19.3 N)

HANDLING

PER PALLET:	6" Roll - 80 rolls, 4000 SF, 1680 lbs
	12" Roll - 40 rolls, 4000 SF, 1680 lbs
	18" Roll - 20 rolls, 3000 SF, 1260 lbs
	24" Roll - 20 rolls, 4000 SF, 1680 lbs
	36" Roll - 10 rolls, 3000 SF, 1260 lbs
	48" Roll - 10 rolls, 4000 SF, 1680 lbs