

DESCRIPTION

BIOFLEX VE is a single component, extended modified bitumen primer specifically for use with hot applied, rubberized asphalt systems like **BIOFLEX SHELTER**. It has low VOC's and is a LEED compliant solvent.

INTENDED USAGE

BIOFLEX VE can be used vertically and horizontally on a variety of surfaces/common building materials such as concrete, masonry and metal. Suitable for application under a wide range of temperatures.

PROPERTIES

VOC Content 60 g/L

Color Black

Solids Content 62.5% (High)

Specific Gravity 0.947

HANDLING

APPLICATION NOTES	<ol style="list-style-type: none">1. For best results use spray application (can be rolled or brushed as well).2. DO NOT cut with diesel or gas. Can be cut with acetone if necessary.3. Lower ambient temperatures or rising humidity will increase relative drying time.4. Stir before users separation may occur from storage.5. Allow for product time to dry to a tacky, "tanning" (or "browning") finish.6. Over application may result in lack of adhesion with substrate or membrane.
COVERAGE RATES	750 - 900 ft. ² /gallon (18 - 22 m ² /L)
SHELF LIFE	Maximum 2 years unopened, > 400F < 900F (> 4.40C < 320C)
CONTAINERS	5 US gal. (18.9L) Pail



LIMITED WARRANTY

BIOFLEX ROOF PRODUCTS warrants this product to be free of defects according to our published literature at time and place of shipment.

DISCLAIMER

The information herein contained is, to the best of our knowledge, accurate and reliable.

BIOFLEX ROOF PRODUCTS cannot, however, guarantee results in connection with the use of this information.

Specifier and User shall be responsible for determining the suitability of the products for specific applications.

BIOFLEX ROOF PRODUCTS copyright 2022

www.bioflexroofs.com

TECHSUPPORT@BIOFLEXROOFS.COM