

DESCRIPTION

BIOFLEX VISCO is a natural, ground walnut thickening agent.

INTENDED USAGE

BIOFLEX VISCO is used to add density to **BIOFLEX NATURA** in situations where vertical applications are necessary such as parapets, up stands, stack vents, through pipes, etc...

PROPERTIES

US Sieve Size 36/60

Grain Size 1.0098 in. - 0.0197 in. (0.25mm - 0.50mm)

Source US grown English walnuts

HANDLING

APPLICATION RATES

Vertical applications > 57° F (14° C) use 5 lbs. (2.27 kgs.) for 1 gal. (3.78 L) of mixed product.
< 57° F (14° C) use 2.5 lbs. (1.14 kgs.) for 1 gal. (3.78 L) of mixed product.

Crack filling & high traffic areas 1 lb. (0.45 kgs.) for 5 gal. (18.9 L) of mixed product.

SHELF LIFE Indefinite if kept dry in low humidity.

CONTAINERS 50 lbs. (22.7 kgs.) per bag.

SHIPPING 40 bags per pallet.

www.bioflexroofs.com

833.425.2441

TECHSUPPORT@BIOFLEXROOFS.COM



LIMITED WARRANTY

BIOFLEX ROOF PRODUCTS warrants this product to be free of defects according to our published literature at time and place of shipment.

DISCLAIMER

The information herein contained is, to the best of our knowledge, accurate and reliable.

BIOFLEX ROOF PRODUCTS cannot, however, guarantee results in connection with the use of this information.

Specifier and User shall be responsible for determining the suitability of the products for specific applications.

BIOFLEX ROOF PRODUCTS copyright 2022

www.**BIOFLEXROOFS**.com

833.425.2441

TECHSUPPORT@BIOFLEXROOFS.COM