

# Safety Data Sheet

## CleanPro 3000W

### 1. Product and company identification

<b>Product name</b>	: CleanPro 3000W
<b>Material uses</b>	: Industrial applications: Well treating agents
<b>Internal code</b>	: OFS3235
<b>System code</b>	: OFS3265
<b>Date of issue/Date of revision</b>	: 2020-11-12
<b>Date of previous issue</b>	: No previous validation
<b>Version</b>	: 1
<b>Supplier</b>	: Highline Energy Services 2264 G Road Grand Junction, CO 81505
<b>Information contact</b>	: +1 970 628-6507
<b>Emergency phone:</b>	: +1 970 628-6507

### Section 2. Hazards identification

<b>OSHA/HCS status</b>	: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
<b>Classification of the substance or mixture</b>	: FLAMMABLE LIQUIDS - Category 3 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) (eyes) - Category 1

#### GHS label elements

##### Hazard pictograms



##### Signal word

: Danger

##### Hazard statements

: H226 - Flammable liquid and vapor.  
H302 + H312 + H332 - Harmful if swallowed, in contact with skin or if inhaled.  
H314 - Causes severe skin burns and eye damage.  
H370 - Causes damage to organs. (eyes)

##### Precautionary statements

**Date of issue/Date of revision** : 2020-11-12

1/14

## Section 2. Hazards identification

<b>Prevention</b>	: P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P241 - Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. P242 - Use only non-sparking tools. P243 - Take precautionary measures against static discharge. P233 - Keep container tightly closed. P271 - Use only outdoors or in a well-ventilated area. P260 - Do not breathe vapor. P270 - Do not eat, drink or smoke when using this product. P264 - Wash hands thoroughly after handling.
<b>Response</b>	: P307 + P311 - IF exposed: Call a POISON CENTER or physician. P304 + P340 + P310 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. P301 + P310 + P330 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. P303 + P361 + P353 + P363 + P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. P302 + P352 + P312 + P362+P364 - IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or physician if you feel unwell. Take off contaminated clothing and wash it before reuse. P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
<b>Storage</b>	: P405 - Store locked up. P403 - Store in a well-ventilated place. P235 - Keep cool.
<b>Disposal</b>	: P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
<b>Hazards not otherwise classified</b>	: None known.
<b>Target organs</b>	: Contains material which causes damage to the following organs: upper respiratory tract, skin, eye, lens or cornea, teeth. Contains material which may cause damage to the following organs: blood, lungs, liver, gastrointestinal tract, cardiovascular system, central nervous system (CNS).

See toxicological information (Section 11)

## Section 3. Composition/information on ingredients

**Substance/mixture** : Mixture

Ingredient name	%	CAS number
methanol	15 - 30	67-56-1
acetic acid	10 - 14.99	64-19-7
Citric acid	5 - 9.99	77-92-9
Nonyl Phenol Ethoxylated	5 - 9.99	127087-87-0
thioglycolic acid	1 - 4.99	68-11-1

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

### Additional information

**Date of issue/Date of revision** : 2020-11-12

2/14

## Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

### Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Remove dentures if any. Wash out mouth with water. Stop if the exposed person feels sick as vomiting may be dangerous. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : Harmful if inhaled.
- Skin contact** : Causes severe burns. Harmful in contact with skin.
- Ingestion** : Harmful if swallowed.

#### Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:  
pain  
watering  
redness
- Inhalation** : No specific data.

## Section 4. First aid measures

**Skin contact** : Adverse symptoms may include the following:  
pain or irritation  
redness  
blistering may occur

**Ingestion** : Adverse symptoms may include the following:  
stomach pains

### Indication of immediate medical attention and special treatment needed, if necessary

**Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

**Specific treatments** : No specific treatment.

**Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### Extinguishing media

**Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.

**Unsuitable extinguishing media** : Do not use water jet.

**Specific hazards arising from the chemical** : Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
carbon dioxide  
carbon monoxide  
sulfur oxides

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

**Flash point** : Closed cup: 30.7°C (87.3°F)

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

## Section 6. Accidental release measures

- For emergency responders** : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Methods and materials for containment and cleaning up**
- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). The spilled material may be neutralized with sodium carbonate, sodium bicarbonate or sodium hydroxide. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

## Section 7. Handling and storage

### Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Keep away from alkalis. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10). Store locked up. Eliminate all ignition sources. Separate from alkalis. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## Section 8. Exposure controls/personal protection

### Control parameters

#### Occupational exposure limits

Ingredient name	Exposure limits
methanol	<p><b>ACGIH TLV (United States, 3/2019). Absorbed through skin.</b>            TWA: 200 ppm 8 hours.            TWA: 262 mg/m<sup>3</sup> 8 hours.            STEL: 250 ppm 15 minutes.            STEL: 328 mg/m<sup>3</sup> 15 minutes.</p> <p><b>OSHA PEL 1989 (United States, 3/1989). Absorbed through skin.</b>            TWA: 200 ppm 8 hours.            TWA: 260 mg/m<sup>3</sup> 8 hours.            STEL: 250 ppm 15 minutes.            STEL: 325 mg/m<sup>3</sup> 15 minutes.</p> <p><b>NIOSH REL (United States, 10/2016). Absorbed through skin.</b>            TWA: 200 ppm 10 hours.            TWA: 260 mg/m<sup>3</sup> 10 hours.            STEL: 250 ppm 15 minutes.            STEL: 325 mg/m<sup>3</sup> 15 minutes.</p> <p><b>OSHA PEL (United States, 5/2018).</b>            TWA: 200 ppm 8 hours.            TWA: 260 mg/m<sup>3</sup> 8 hours.</p>
acetic acid	<p><b>ACGIH TLV (United States, 3/2019).</b>            TWA: 10 ppm, 0 times per shift, 8 hours.            TWA: 25 mg/m<sup>3</sup>, 0 times per shift, 8 hours.            STEL: 15 ppm, 0 times per shift, 15 minutes.            STEL: 37 mg/m<sup>3</sup>, 0 times per shift, 15 minutes.</p> <p><b>OSHA PEL 1989 (United States, 3/1989).</b>            TWA: 10 ppm, 0 times per shift, 8 hours.            TWA: 25 mg/m<sup>3</sup>, 0 times per shift, 8 hours.</p> <p><b>NIOSH REL (United States, 10/2016).</b>            TWA: 10 ppm, 0 times per shift, 10 hours.            TWA: 25 mg/m<sup>3</sup>, 0 times per shift, 10 hours.            STEL: 15 ppm, 0 times per shift, 15 minutes.            STEL: 37 mg/m<sup>3</sup>, 0 times per shift, 15 minutes.</p> <p><b>OSHA PEL (United States, 5/2018).</b>            TWA: 10 ppm, 0 times per shift, 8 hours.            TWA: 25 mg/m<sup>3</sup>, 0 times per shift, 8 hours.</p>
thioglycolic acid	<p><b>ACGIH TLV (United States, 3/2019). Absorbed through skin.</b>  <b>Skin sensitizer.</b>            TWA: 1 ppm 8 hours.</p> <p><b>OSHA PEL 1989 (United States, 3/1989). Absorbed through skin.</b>            TWA: 1 ppm 8 hours.            TWA: 4 mg/m<sup>3</sup> 8 hours.</p> <p><b>NIOSH REL (United States, 10/2016). Absorbed through skin.</b>            TWA: 1 ppm 10 hours.            TWA: 4 mg/m<sup>3</sup> 10 hours.</p>

## Section 8. Exposure controls/personal protection

- Appropriate engineering controls** : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Individual protection measures**
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** : Liquid.
- Color** : Clear. Colorless.
- Odor** : Pungent. [Slight]
- Odor threshold** : Not available.
- pH** : 1.3 to 2.3
- Melting point/freezing point** : Not available.

**Date of issue/Date of revision** : 2020-11-12

## Section 9. Physical and chemical properties

<b>Boiling point</b>	: Lowest known value: 64.7°C (148.5°F) (methanol). Weighted average: 100.14°C (212.3°F)
<b>Flash point</b>	: Closed cup: 30.7°C (87.3°F)
<b>Evaporation rate</b>	: Highest known value: 2.1 (methanol) Weighted average: 1.85 compared with butyl acetate
<b>Flammability (solid, gas)</b>	: Not available.
<b>Lower and upper explosive (flammable) limits</b>	: Greatest known range: Lower: 6% Upper: 44% (methanol)
<b>Vapor pressure</b>	: Highest known value: 16.9 kPa (127 mm Hg) (at 20°C) (methanol). Weighted average: 6.37 kPa (47.78 mm Hg) (at 20°C)
<b>Vapor density</b>	: Highest known value: 3.2 (Air = 1) (thioglycolic acid). Weighted average: 1.6 (Air = 1)
<b>Density</b>	: 0.991 g/cm <sup>3</sup>
<b>Specific gravity</b>	: 0.991
<b>Solubility</b>	: Easily soluble in the following materials: cold water, hot water, methanol.
<b>Partition coefficient: n-octanol/water</b>	: Not available.
<b>Auto-ignition temperature</b>	: Lowest known value: 315°C (599°F) (thioglycolic acid).
<b>Decomposition temperature</b>	: Not available.
<b>Viscosity</b>	: Not available.

## Section 10. Stability and reactivity

<b>Reactivity</b>	: No specific test data related to reactivity available for this product or its ingredients.
<b>Chemical stability</b>	: The product is stable.
<b>Possibility of hazardous reactions</b>	: Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	: Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
<b>Incompatible materials</b>	: Attacks many metals producing extremely flammable hydrogen gas which can form explosive mixtures with air. Reactive or incompatible with the following materials: alkalis oxidizing materials
<b>Hazardous decomposition products</b>	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## Section 11. Toxicological information

### Information on toxicological effects

#### Acute toxicity

## Section 11. Toxicological information

Product/ingredient name	Test	Species	Result	Dose
methanol	-	Rat	LC50 Inhalation Gas.	145000 ppm 1 hours
	-	Rat	LC50 Inhalation Gas.	64000 ppm 4 hours
	-	Rabbit	LD50 Dermal	15800 mg/kg -
acetic acid	-	Rat	LD50 Oral	5600 mg/kg -
	-	Rat	LC50 Inhalation Vapor	11000 mg/m <sup>3</sup> 4 hours
	-	Rabbit	LD50 Dermal	1060 mg/kg -
Citric acid	-	Rat	LD50 Oral	3310 mg/kg -
	-	Rat	LD50 Oral	3 g/kg -
	-	Rabbit	LD50 Dermal	>3000 mg/kg Key literature references and sources for data
Nonyl Phenol Ethoxylated	-	Rat	LD50 Oral	>5000 mg/kg -
	-	Rat	LC50 Inhalation Vapor	210 mg/m <sup>3</sup> 4 hours
	-	Rat	LD50 Oral	114 mg/kg -

### Potential chronic health effects

Not available.

### Irritation/Corrosion

Product/ingredient name	Test	Species	Result
Citric acid	-	Rabbit	Eyes - Severe irritant -
	-	Rabbit	Skin - Mild irritant -
	-	Rabbit	Skin - Moderate irritant -

### Sensitization

Not available.

### Mutagenicity

Not available.

### Carcinogenicity

Not classified or listed by IARC, NTP, OSHA, EU and ACGIH.

### Reproductive toxicity

Not available.

### Teratogenicity

Not available.

### Specific target organ toxicity (single exposure)

## Section 11. Toxicological information

Name	Category	Route of exposure	Target organs
methanol	Category 1	Inhalation	eyes

### Specific target organ toxicity (repeated exposure)

Not available.

### Aspiration hazard

Not available.

## Section 12. Ecological information

### Toxicity

Product/ingredient name	Result	Species	Exposure
methanol	Acute EC50 16.912 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 22200 to 23400 mg/l Fresh water	Daphnia - Daphnia obtusa - Neonate	48 hours
	Acute LC50 2500000 µg/l Marine water	Crustaceans - Crangon crangon - Adult	48 hours
	Acute LC50 100 mg/l Fresh water	Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling)	96 hours
acetic acid	Chronic NOEC 9.96 mg/l Marine water	Algae - Ulva pertusa	96 hours
	Acute EC50 73400 µg/l Fresh water	Algae - Navicula seminulum	96 hours
	Acute EC50 65 mg/l	Daphnia	48 hours
	Acute LC50 32 mg/l Marine water	Crustaceans - Artemia salina	48 hours
	Acute LC50 75 mg/l	Fish - Lepomis macrochirus	96 hours
	Acute LC50 79 mg/l	Fish	96 hours
Citric acid	Acute LC50 88 mg/l	Fish	96 hours
	Acute LC50 160000 µg/l Marine water	Crustaceans - Carcinus maenas - Adult	48 hours
Nonyl Phenol Ethoxylated	Acute EC10 0.0251 mg/l	Algae	72 hours
	Acute EC50 0.0033 mg/l	Algae	72 hours
	Acute EC50 0.027 mg/l	Algae	96 hours
	Acute LC50 0.11 mg/l	Daphnia	48 hours
	Acute LC50 0.136 mg/l	Fish	96 hours
	Chronic NOEC 100 mg/m <sup>3</sup>	Daphnia	21 days
thioglycolic acid	Chronic NOEC 6 mg/m <sup>3</sup>	Fish	91 days
	Acute LC50 30000 µg/l Fresh water	Fish - Pimephales promelas	96 hours

### Persistence and degradability

Product/ingredient name	Test	Result
methanol	OECD 301D Ready Biodegradability - Closed Bottle Test	99 % - 28 days

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
methanol	-	-	Readily
acetic acid	-	-	Readily
Citric acid	-	-	Readily
Nonyl Phenol Ethoxylated	-	-	Not readily

### Bioaccumulative potential




## Section 12. Ecological information

Product/ingredient name	LogP <sub>ow</sub>	BCF	Potential
methanol	-0.77	<10	low
acetic acid	-0.17	-	low
Citric acid	-1.72	-	low
Nonyl Phenol Ethoxylated	5.39	37	low
thioglycolic acid	-2.99	-	low

## Section 13. Disposal considerations

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

	DOT Classification	IMDG	IATA
<b>UN number</b>	UN2920	UN2920	UN2920
<b>UN proper shipping name</b>	Corrosive liquids, flammable, n. o.s. (acetic acid, methanol) RQ (methanol, acetic acid)	CORROSIVE LIQUID, FLAMMABLE, N.O.S. (methanol, acetic acid)	Corrosive liquid, flammable, n. o.s. (acetic acid, methanol)
<b>Transport hazard class(es)</b>	8 (3) 	8 (3) 	8 (3) 
<b>Packing group</b>	II	II	II
<b>Environmental hazards</b>	No.	No.	No.
<b>Additional information</b>	<p><b>Reportable quantity</b> 20000 lbs / 9080 kg [2420.5 gal / 9162.5 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.</p> <p><b>Limited quantity</b> Yes.</p> <p><b>Packaging instruction</b> Exceptions: 154. Non-bulk: 202. Bulk: 243.</p>	<p><b>Emergency schedules</b> F-E, S-C</p> <p><b>Special provisions</b> 274</p> <p><b>IMDG Code Segregation group</b> 1 - Acids</p>	

## Section 14. Transport information

**Quantity limitation** Passenger aircraft/rail: 1 L. Cargo aircraft: 30 L.  
**Special provisions** B2, IB2, T11, TP2, TP27

**Special precautions for user** : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## Section 15. Regulatory information

**U.S. Federal regulations** : **United States inventory (TSCA 8b):** All components are listed or exempted.

**Clean Air Act Section 112** : Listed  
 (b) Hazardous Air Pollutants (HAPs)

### SARA 302/304

#### Composition/information on ingredients

Name	%	EHS	SARA 302 TPQ		SARA 304 RQ	
			(lbs)	(gallons)	(lbs)	(gallons)
ethylene oxide	0 - 0.09	Yes.	1000	-	10	-

**SARA 304 RQ** : 20000000 lbs / 9080000 kg [2420466.4 gal / 9162462.2 L]

### SARA 311/312

**Classification** : Fire hazard  
 Immediate (acute) health hazard

#### Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
methanol	15 - 30	Yes.	No.	No.	Yes.	No.
acetic acid	9.99 - 14.99	Yes.	No.	No.	Yes.	No.
Citric acid	4.99 - 9.99	No.	No.	No.	Yes.	No.
Nonyl Phenol Ethoxylated	4.99 - 9.99	No.	No.	No.	Yes.	No.
thioglycolic acid	0.99 - 4.99	No.	No.	No.	Yes.	No.

### SARA 313

	Product name	CAS number	%
<b>Form R - Reporting requirements</b>	methanol	67-56-1	15 - 30
<b>Supplier notification</b>	methanol	67-56-1	15 - 30

**Date of issue/Date of revision** : 2020-11-12

## Section 15. Regulatory information

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

### State regulations

- Massachusetts** : The following components are listed: METHANOL; ACETIC ACID; THIOGLYCOLIC ACID
- New York** : The following components are listed: Methanol; Acetic acid
- New Jersey** : The following components are listed: METHYL ALCOHOL; METHANOL; ACETIC ACID; ETHANOIC ACID; THIOGLYCOLIC ACID; ACETIC ACID, MERCAPTO-
- Pennsylvania** : The following components are listed: METHANOL; ACETIC ACID; ACETIC ACID, MERCAPTO-
- California Prop. 65** : **WARNING:** This product can expose you to chemicals including Ethylene oxide, which is known to the State of California to cause cancer and birth defects or other reproductive harm. This product can expose you to chemicals including Methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level	Contains : % or ppm
methanol ethylene oxide	No. Yes.	Yes. Yes.	Yes.	Yes. Yes.	≥10 - ≤25 <0.1

### International lists

#### National inventory

#### Australia inventory (AICS)

#### Canada inventory

#### China inventory (IECSC)

#### Europe inventory

#### Japan inventory

#### New Zealand Inventory of Chemicals (NZIoC)

#### Philippines inventory (PICCS)

#### Korea inventory (KECI)

#### Taiwan inventory (TCSI)

#### United States inventory (TSCA 8b)

- : All components are listed or exempted.
- : All components are listed or exempted.
- : All components are listed or exempted.
- : All components are listed or exempted.
- : **Japan inventory (ENCS):** All components are listed or exempted.
- Japan inventory (ISHL):** Not determined.
- : All components are listed or exempted.
- : All components are listed or exempted.
- : All components are listed or exempted.
- : All components are listed or exempted.
- : All components are listed or exempted.
- : All components are listed or exempted.

Our REACH (pre-) registrations DO NOT cover the following:

1. The manufacture of these products by our company outside the EU unless covered by the Only Representative provisions, and
2. The importation of these products into Europe by other companies. Re-importation by other companies is not covered by our (pre-) registrations

Customers and other third parties importing and/or re-importing our products into Europe will need either:

- Their own (pre-) registration for substances contained in the imported product, or constituent monomers (imported above 1 tonne per year and >2% by weight) in the case of imported polymers, or
- In the case of importation only, to make use of the "Only Representative" provisions, if available.

## Section 16. Other information

### Hazardous Material Information System (U.S.A.)

Health	/	3
Flammability		3
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

### National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

### History

<b>Date of printing</b>	: 2020-11-12
<b>Date of issue/Date of revision</b>	: 2020-11-12
<b>Date of previous issue</b>	: No previous validation
<b>Version</b>	: 1
<b>Key to abbreviations</b>	: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = Intermediate Bulk Container IMDG = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) UN = United Nations

📌 Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.