



Lean Basic Trolley LC12060

- The Lean Basic Trolley is a multipurpose load carrier for both internal and external logistics. Dimensionally optimised for standard SLC boxes.
- The Lean Basic Trolley is compatible with all Lean-Tech towable trolleys. It is the cheapest solution for internal logistics and an excellent choice for forklift-free environments with very low maintenance requirements. Lean Basic Trolleys can be used in almost all industries.
- As all our products, the Lean Shelf Trolleys are equipped with directional stability, even when driving around curves.
- Loading from both sides enables a streamlined logistics process.
- Flat and Tilted shelves can be changed installed easily.



External dimensions (l x w x h) : 1290 x 605 x 1650 mm

Shelf Surface Area (l x w) : 1200 x 600 mm

Loading capacity in kg : 500 kg

Shelf Loading Capacity in kg : 390 kg

-Level 0 : 200 kg

-Level 1 :

-Level 2 :

-Level 3 :

Max Towing Capacity in kg : 2000 kg

Max. Towing Speed : 6 km/hr

Technical Features

- Electrostatic powder painted chassis and Electro-galvanized body.
- Info boards on both sides
- 2 swivel castors and 2 fixed castors, Ø 150 mm, elastic solid rubber, 85° Shore A double ball bearing in rotating assembly and ball bearing in hub and foot protection on all castors.
- Forklift safety guides.

Optional:

- Electro-galvanized Chassis
- Electro-galvanized flat and tilted shelves
- Electrically conductive castors and antistatic strap