



Shelf Trolley MD10060

Basic features:

- Shelf Trolley is a unique tugger train solution for internal logistics and an excellent choice for forklift-free environments. It can be used in almost all industries. Shelf Trolley can travel both individually by pulling and also in the towed train.
- As all our products, the Shelf Trolleys are equipped directional stability, even when driving around curves.
- Loading from both sides enables a streamlined logistics process.
- Tilted shelves can be changed with flat shelves and enables direct line material feeding.



External dimensions (l x w x h) : 1190 x 605 x 1650 mm

Shelf Surface Area (l x w) : 1000 x 600 mm

Loading capacity in kg : 500 kg

Shelf Loading Capacity in kg

-Level 0 : 200 kg

-Level 1 : 100 kg

-Level 2 : 100 kg

-Level 3 : 100 kg

Max Towing Capacity in kg : 2400 kg

Max. Towing Speed : 6 km/hr

Technical Features

- Electro-galvanized body.
- Foot protection on all castors
- Info boards on both sides
- 2 swivel castors and 2 fixed castors, Ø 150 mm, elastic solid rubber, 85° Shore A double ball bearing in rotating assembly and ball bearing in hub
- Drawbar system

Optional:

- Stainless steel body and wheels
- Electrically conductive castors and antistatic strap
- Integrated hand brake