INTIMIDATOR™ 12XP 12" Capacity Hand-Fed Chipper

Tree care professionals, municipalities and rental companies seeking a **compact-yet-powerful** 12" capacity drum chipper turn to the Intimidator 12XP. This impressive chipper features a large 24" diameter chipping drum and at 5,500 pounds it is **easily towable**. Built strong using the highest quality components and assembled with solid welded construction, the Intimidator 12XP will **outperform and outlast** all other 12" capacity drum chippers on the market.

12XP

PERFORMANCE OF A LIFETIME

Bandit chippers have proven over time to be the best economical decision you can make for a long-term investment in a brush chipper. Longevity is key. Like all Bandit models, the 12XP is engineered for maximum performance and equipped with features that increase operator productivity over time.

ELIMINATE TRIM WORK

Bandit's unique slide box feed system and powerful 17" wide by 7.5" diameter dual horizontal feed rollers grab, crush and compress limby material, easily guiding it to the drum. Options for a hydraulic feed wheel lift cylinder and hydraulic winch help process material faster.

MAXIMIZE YOUR UPTIME

The most common maintenance items are easy to access on Bandit chippers, so daily maintenance is quick and simple. Bolt-in knives are easy to change through the chipper hood, and all service areas are conveniently located, including all grease points.

and options are subject to change without notice, and were current at the time of printing. Dimens

REDUCE YOUR FUEL COSTS

The 12XP's drum turns at a lower RPM with greater torque, and the synchronized feed system never underfeeds or forces material against the drum. The result is a more efficiently fed chipper that reduces idle time, and translates to fuel savings up to 30 percent, gas or diesel.



6750 Millbrook Rd. • Remus, MI 49340 • 1-800-952-0178 FIND US ONLINE

Hand-Fed Chippers • **Stump Grinders** • Whole Tree Chippers The Beast[®] Horizontal Grinders • Track Carriers • Attachments

INTIMIDATOR[™] 12XP

SPECIFICATIONS

MEASUREMENTS	TOWABLE		TRACK	
Length (tray open):	16' 2"	492.8 cm	13' 9"	419.1 cm
Width:	6' 8"	203.2 cm	6' 5"	195.6 cm
Height:	8' 2"	248.9 cm	8'	243.8 cm
Weight:	5,500 lbs.	2,495 kg	8,000 lbs.	3,629 kg
Engines:	49.6 HP - 145 HP (36.8 - 108.1 kW)			
Fuel Tank:	25 gal.	94.6 L	50 gal.	189.3 L
Hydraulic Tank:	12 gal.	45.4 L	50 gal.	189.3 L

UNDERCARRIAGES

Towable: Single 7,000 pound Torflex axle with (2) 235/80R 16" tires mounted on white spoke rims

Track: Caterpillar 303CR rubber track undercarriage

Standard & Custom Colors Available

Choose from two standard colors, or select a custom color to match your fleet.



COMMITTED TO QUALITY & SERVICE

The Bandit Backbone™ Support

The Bandit Backbone is Bandit's commitment to customer service and support. It's always been a cornerstone of Bandit's philosophy, and today that backbone is stronger than ever. If you own a Bandit hand-fed chipper – regardless the age, hours, or warranty status – the Bandit Backbone is here to support you.

We Are Here to Support You

There are nearly 200 dealer locations in the US and over 60 international dealers to support you. They are factory trained. Plus we have an experienced parts and service department supporting you and our dealers.



DIMENSIONS				
Capacity:	12"	30.48 cm		
Opening:	14.25" high x 17" wide	36.2 cm x 43.2 cm wide		
Drum:	24" dia. x 18.75" wide	61 cm dia. x 47.6 cm wide		
RPM:	Approximately 1,530 RPM			

Hitch: 2-1/2" pintle hitch

Discharge: Height-adjustable, 360° hand crank swivel with 12" (30.5 cm) adjustable chip deflector

Feed System: Slide box feed system with (2) 17" (43.2 cm) adjustable down pressure springs, (2) 7-1/2" diameter x 17" wide feed wheels (19.05 cm x 43.18 cm) powered by (2) 15 CID hydraulic motors

Frame: Mainframe is constructed of 3/16" x 2" x 4" rectangular tubing (0.48 x 5.1 x 10.2 cm)



INTIMIDATOR™ 12XP FEATURES

- Rope/Line Shear Device (standard) Provides an improved chance that rope or lines inadvertently entering the chipper may be cut
- Last Chance Cables (standard) Stops/reverses the feed wheel when pulled in case of an emergency
- Operator Safety Control Bar (standard) Wraps around 3 sides of the infeed chute & controls the direction of feed wheels
- Wood Pusher Paddle (standard) Used to feed small wood debris into the chipper
- Chipper Hood Pin w/Padlock (standard) Prevents unauthorized access to the disc or drum
- Chipper Hood Engine Disable Plug (standard) Prevents engine from being started without the hood pin in place
- Hydraulic Bottom Bump Bar (option) Stops feed wheels via mechanical connection when bumped, diverting hydraulic power away from the feed wheels

Bandit Offers a Complete Line of Tree Care Equipment: Hand-Fed Chippers • Stump Grinders • Whole Tree Chippers The Beast[®] Horizontal Grinders • Track Carriers • Attachments