

TRAN-CSB10-xx (PROTOCOL TRANSLATOR)

Bluetooth enabled protocol translator

Created By



Powered By **CASAMBI**

Features & Benefits:

- 1-4 Channel BLE/0-10V dimming controller with 2A switched live output
- Controls a maximum of 5 drivers
- Bluetooth beacons
- Dimensions: 183mm x 49mm x 35mm
72 mm x 52mm x 35mm



Product Description

Bluetooth enabled translator converts BLE signal to 0-10v dimming output with 2A switched live output. Suitable for use with all 0-10v and 1-10v dimming drivers.

TRAN-CSB10-xx (PROTOCOL TRANSLATOR)

Bluetooth enabled protocol translator

Created By



Powered By CASAMBI

Specifications:

AC Input:

Voltage range: 120-277VAC

Channel output:

0-10V 1 or 4 channels

Operating conditions:

Ambient temperature (ta) -4°F to +113°F (-20°C to +45°C)
Max. case temperature (tc) +158°F (+70 °C)
Storage temperature -13°F to +158°F (-25°C to +70°C)
Humidity 0-80% non-condensing

Safety Compliance:

Ingress Protection IP20 (indoor use only)
Protection Class Class 1
UL Listed

Mechanical:

Dimensions 183mm x 49mm x 35mm
72 mm x 52mm x 35mm

TRAN-CSB10-xx (PROTOCOL TRANSLATOR)

Bluetooth enabled protocol translator

Created By



Powered By CASAMBI

Ordering Information:

Part Number:	Description:
TRAN-CSB10-E-SL	1 Channel BLE/10V Dimmer, 2A switched live output. 120-277VAC. Wires accessible via side of module.
TRAN-CSB10-E	1 Channel BLE/10V Dimmer. 120-277VAC. Wires accessible via side of module.
TRAN-CSB10-J-SL	1 Channel BLE/10V Dimmer, 2A switched live output. 120-277VAC. Wires accessible via back of module.
TRAN-CSB10-J	1 Channel BLE/10V Dimmer. 120-277VAC. Wires accessible via back of module.
TRAN-CSB10-4	4 Channel BLE/10V Dimmer, 2A switched live output. 120-277VAC.
TRAN-CSB10-2	2 Channel BLE/10V Dimmer, 2A switched live output. 120-277VAC.