

TRAN-ING10-xx

Wirepas enabled lighting controller

Created By



Powered By



Features & Benefits:

- 1-4 Channel Wirepas/0-10V dimming controller with 2A switched live output
- Controls a maximum of 5 drivers
- Bluetooth beacons
- Dimensions: 183mm x 49mm x 35mm
72 mm x 52mm x 35mm



Product Description

Wirepas enabled translator converts INGY signal to 0-10v dimming signal with 2A switched live output. Suitable for use with all 0-10V and 1-10V dimming drivers.

TRAN-ING10-xx

Wirepas enabled lighting controller

Created By



Powered By



Specifications:

AC Input:

Voltage range: 120-277VAC

Channel output:

0-10V 1 or 4 channels

Operating conditions:

Ambient temperature (ta) -4°F to +113°F (-20°C to +45°C)
Max. case temperature (tc) +158°F (+70 °C)
Storage temperature -13°F to +158°F (-25°C to +70°C)
Humidity 0-80% non-condensing

Safety Compliance:

Ingress Protection IP20 (indoor use only)
Protection Class Class 1
UL Listed

Mechanical:

Dimensions 183mm x 49mm x 35mm
72 mm x 52mm x 35mm

TRAN-ING10-xx
Wirepas enabled lighting controller

Created By



Powered By



Ordering Information:

Part Number:	Description:
TRAN-ING10-E-SL	1 Channel Wirepas/10V Dimmer, 2A switched live output. 120-277VAC. Wires accessible via side of module.
TRAN-ING10-E	1 Channel Wirepas/10V Dimmer. 120-277VAC. Wires accessible via side of module.
TRAN-ING10-J-SL	1 Channel Wirepas/10V Dimmer, 2A switched live output. 120-277VAC. Wires accessible via back of module.
TRAN-ING10-J	1 Channel Wirepas/10V Dimmer. 120-277VAC. Wires accessible via back of module.
TRAN-ING10-4	4 Channel Wirepas/10V Dimmer, 2A switched live output. 120-277VAC.
TRAN-ING10-2	2 Channel Wirepas/10V Dimmer, 2A switched live output. 120-277VAC.