

PSC-WCM-300-BLE-IG

10amp Relay and 0-10V Dimmer

Created By



Powered By



Features & Benefits:

- 100-277VAC Input Voltage
- Wireless Wirepas Mesh
- 0-10V Output to LED Driver
- Power metering with +/-1% accuracy
- Zero-Crossing
- IP20 Rated
- UL60730, UL2043 Pending



Product Description

The Wireless Line Voltage Fixture and Room Controller allows for 0-10V Output to LED Driver, and is made to fit into a Wirepas mesh system.

For input voltage of 100-277VAC, this unit is controlled wirelessly via Wirepas Mesh module allowing for wireless dimming of LED lighting and seamless integration of Wirepas Mesh software solutions. The small physical size allows for this unit to be placed within the fixture, it also comes with threaded nipple for junction box mounting when required.

PSC-WCM-300-BLE-IG

10amp Relay and 0-10V Dimmer

Created By



MCWONG

Powered By



Summary

Product Type Wireless Line Voltage Fixture and Room Controller

Input Voltage 100-277VAC 50/60Hz

Load (10A Relay) @120/277Vac 720W, incandescent
@120/277Vac 10A, electronic ballast

Load (16A Relay) @120/277Vac 1200W, incandescent
@120/277Vac 16A, electronic ballast

0-10V Dimming 3 mA sink

Max Wireless Range* 49 ~ 65ft (15 ~ 20m)

Operating Temperature -40° C to 70°C

Storage Temperature -40° C to 85°C

Relative Humidity 90-95% non-condensing at 30°C

Mounting Fixture or ceiling mount

Color White

