PALMIERI GENERAL

MODEL NUMBER	PRODUCT	WIDTH	DEPTH	HEIGHT	WEIGHT	VOLUME	PRICE	DESCRIPTION
GN-120-S GN-120-D	Revolving Dictionary Stand, Single Faced Revolving Dictionary Stand, Double Faced	21"	12"	9"	14 Lbs. 16 Lbs.	2 Cu.Ft	\$ 877 \$ 1,275	Top constructed from 3/4" thick 3-ply particleboard, faces veneered. Edges banded with 1/4" solid external banding. Top to receive a 3/8" thick x 1/2" high solid retaining lip. Top is sloped at a 12 degree angle. Base, 17" wide x 10" deep x 5-1/2" high, constructed of 3/4" particleboard, all faces veneered. A ball bearing swivel plate is mounted to the underside of the base and fixed to a 3/4" thick x 12" wide x 8" deep wood plate.
GN-905-5	Map Case: 5 Drawer Large	51″	41"	221/4"	310 Lbs.	33 Cu.Ft	\$ 5,106	TOP: Constructed from 1" thick 3-ply particleboard core. Top surface with a high pressure laminate sheet, Surrounding edges shall receive a 1/4" x 1-1/4" solid internal edge band.
GN-905-10	Map Case: 10 Drawer Large	51"	41"	39 ³ /8"	560 Lbs.	61 Cu.Ft	\$ 9,228	CABINET CONSTRUCTION: Sub top, bottom and side panels constructed from 3/4" veneer plywood. Front edges banded 1/4" external solid, all edges eased. 4" high base comes complete with black ribbed rubber.
								DRAWERS: 5 drawers (10 drawers for model G-905-10) 47" wide x 37" deep x 2" high constructed from 1/2" mahogany veneer core. Drawer front constructed from 3/4" thick x 2" high solid. Drawers operate on 32" long full extension blum slides.
GN-154	Map Case	391/2"	27″	363/8"	215 Lbs.	24 Cu.Ft	\$ 7,603	CABINET CONSTRUCTION: Top, bottom and side panels constructed from 3/4" veneer plywood, front edges banded 1/4" external solid. Top surface to be a high pressure laminate.
								DRAWERS: Six drawers 37" wide x 25" deep x 2-13/16" high constructed from 1/2" mahogany veneer core, drawer front constructed from 3/4" x 4" high solid. Drawers operate on 24" long full extension Blum slides.
								WOOD BASE: A solid apron base 3/4" x 3-3/8"
								LEG ASSEMBLY: Legs are 1-3/4" x 1-3/4" glued-up solid stock, all edges eased.
								GLIDES: Each leg shall be fitted with a threaded T-nut to accept a 1-5/8" diameter cushioned glide complete with a 1-1/2" x 3/8" threaded stem.

