



ESTPLY FORM

Strong forming board for concrete casting

ESTPLY FORM is a birch plywood panel coated with smooth phenolic overlay on both sides.

The dimensional stability makes it a perfect panel for system formwork. Because of the low maintenance need, it is also an ideal board for different kind of wall and lining applications.

We take the carbon emissions seriously. Our birch logs come only from well managed forests, and we process the precious raw material with care and respect.



Several re-uses



Easy to clean



Strong

ESTPLY FORM

Standard size	1500/1525 mm x 2500/3000/3050/3300 mm			
Size Tolerance	LENGTH/WIDTH	TOLERANCE		
	<1000 mm	±1 mm		
	1000–2000 mm	±2 mm		
	>2000 mm	±3 mm		
Standard Thickness	6.5-> 50 mm			
Thickness Tolerance	NOMINAL THICKNESS (mm)	THICKNESS TOLERANCE		NUMBER OF PLYES
		min. (mm)	max. (mm)	
	4	3.5	4.1	3
	6.5	6.1	6.9	5
	9	8.8	9.5	7
	12	11.5	12.5	9
	15	14.3	15.3	11
	18	17.1	18.1	13
	21	20.0	20.9	15
	24	22.9	23.7	17
	27	25.2	26.8	19
	30	28.1	29.9	21
	35	33.5	35.5	25
	40	38.8	41.2	29
45	43.6	46.4	33	
50	48.5	51.5	35	
Density	kg/m ³ 640-700			
Glue type	Phenol formaldehyde adhesive			
Machining	Estply plywood panels can be machined according to customer specification			
Other Data	Chain of Custody, EN 13986, EN 636 1-2-3 S			
Coating	120-400g			
Edge treatment	Coating related			