



# TuffTex Materials

RESTORATION MADE EASY




# RepPhalt FS

Fast Setting Permanent Asphalt Repair


**TuffTex Materials**



**TuffTex Materials**  
RESTORATION MADE EASY



Saw-Cut or  
Feather-Edge!



All-in-one kit,  
easy install!



Ready for  
traffic in 30 min

## RepPhalt FS

### FEATURES:

- Simple placement
- Easy, just add water
- Strongest cold-mix asphalt sold in the U.S.
- Virtually permanent repair
- Eliminates repeated cold patch repairs
- Environmentally friendly
- Tested temperature installation range 12 - 122 °F
- Traffic ready immediately
- Can be sealed after 1 day
- Fully cured in 24 hours

### USES:

- Expansion, Seismic joints
- Asphalt & Concrete Roads
- Potholes
- Driveways
- Walkways
- Parking Lots
- Carious utility operations
- Manhole Repairs
- Bridge Joints

TuffTex Materials  
2209 Donley Drive  
Austin, TX 78758  
Office: (512) 617-7334



## Combined Aggregate Gradation Ranges

1/2"	97-100%
3/8"	83-100%
#4	58-80%
#8	42-62%
#30	20-40%
#100	5-20%
#200	2-9%

## Absorption

ASTM C-127, 128

2.5% max

## 50 lb. Pail Usage Guide

Repair Area Dimension	Hole Depth	Total Pails Needed
2' x 2'	2"	2
2' x 2'	3"	3
2' x 2'	4"	4
3' x 4'	2"	6
3' x 5'	2"	7
3' x 3'	4"	8



**Steps**



**Clean**



**Pour**



**Add Water**



**Tamp**



**TuffTex Materials**  
RESTORATION MADE EASY



## EXTENSIVE INSTALLATION INSTRUCTIONS FOR EASE OF USE ARE AVAILABLE AND RECOMMENDED!

### **CAUTION:**

#### **READ SDS PRIOR TO USING PRODUCT**

Use with adequate ventilation. Wear protective clothing, gloves, and eye protection. (Goggles, Safety Glasses and/or Face Shield) Keep out of the reach of children. Do not take internally. In case of ingestion, seek medical help immediately. May cause skin irritation upon contact, especially if prolonged or repeated exposure. If skin contact occurs, wash immediately with soap and water and seek medical help as needed. If eye contact occurs, flush immediately with clean water and seek medical help as needed. Dispose of waste material in accordance with federal, state, and local requirements. Cured resins are innocuous. Dispose of waste material in accordance with federal, state, and local requirements.

### **WARRANTY:**

Due to the use of this product beyond our control, we assume no liability for damages of any kind, and the user accepts the product "as is" and without warranties, expressed or implied, from either TuffTex Materials or its agents. The suitability of the product for an intended use shall be solely up to the user. Our only obligation shall be to replace or pay for any material proved defective, with our liability limited to the purchase price of materials supplied by us.

### **DISCLAIMER:**

Refer to the MSDS sheet before use. The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of TuffTex Materials. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Published technical data and instructions are subject to change without notice. Contact your local TuffTex distributor or technical representative for additional technical data and instructions.

### **OSHA Status:**

This Material Safety Data Sheet (MSDS) has been prepared in compliance with the federal OSHA Hazard Communication Standard 29 CFR 1910.1200. This product is not considered to be a hazardous chemical under that standard.

**TuffTex Materials**