



TuffTex Materials
RESTORATION MADE EASY



WATERPROOFING & COATING SYSTEMS

TuffTex Materials

2209 Donley Drive

Austin, TX 78758

Office: (512) 617-7334



TuffTex Materials
RESTORATION MADE EASY



Biodegradable Prep Etch prepares the floor to CSP 3

Vertical & Horizontal membranes

Many choices of colors & textures

WATERPROOFING & COATINGS

Many of our Systems Features

- Non-slip finishes
- Exceptional one day and ultimate physicals
- Extremely durable bonds
- Easy to mix and apply
- Pre-measured packaging of components
- Ability to span shrinkage cracks
- Substantial savings over standard built up systems
- Rapid opening to traffic
- No special equipment required
- On-site training offered
- Good chemical resistance
- Self-Priming in most conditions
- Rapid strength development
- Resistant to automotive fluids
- Low or No VOC's
- Extends the service life of decks

Uses:

- Parking Decks, Ramps
- Walk-Ways, Balconies
- Swimming Pool Non Slip Decks
- Garages, Warehouse Docks
- Bridge Decks, Safety Lanes
- Below Grade, Water Tanks
- Between Slab Waterproofing

TuffTex Materials
2209 Donley Drive
Austin, TX 78758
Office: (512) 617-7334



TuffTex Materials
RESTORATION MADE EASY

RepDeck SOS is the fix all for most every water leaking situation or the need for a quick permanent & versatile coating. 1 component, water catalyzed for faster cure, apply at any thickness, fast drying, 400% elongation, primerless, non-gassing, and tremendous bond.

RepDeck SD is the workhorse of coatings. 2 part, fast drying, primerless, Heavy Traffic area, ultimate properties deck coating, can be applied to any surface. Opens to traffic in half the time of others coatings.

RepDeck BC is the slower setting base coat version of **SD**.

RepDeck TC is a 2 part, fast setting, hybrid aliphatic polyurea elastomeric membrane, workhorse top coating for all systems.

RepCoat PW-H Two part horizontal grade, low odor, NSF Approved, trowel or sprayed, potable water protective lining for tanks & cisterns.

RepCoat PW-V Two part vertical grade, low odor, NSF Approved, trowel or sprayed, potable water protective lining for tanks & cisterns.

RepPrime #1 Low odor, multi- use, best overall primer. (1:1)

RepPrime #3 Best primer for decks & new/old bonding. (1:1)

RepDeck H One part horizontally applied, 350 % elongation, between slabs, lower viscosity waterproof membrane.

RepDeck V One part vertical applied, 350 % elongation, waterproof membrane.

RepTape JC Adhesive backed tape for expansion joints & wide cracks.

RepTape CT Adhesive backed tape for very small joints & cracks.

RepTape MT Mesh Fabric for embedment.

TuffTex Coating & Waterproofing

At **TuffTex Materials**, we strive to, and succeed in, being more than just a product manufacturer meeting traditional specifications with outdated technology many other producers focus on. Rather, we choose to be a leader in Material Quality while producing New Innovative State of the Art polymer coating and chemical systems. **TuffTex Materials** offers many various systems for the Construction & Restoration Industry. We excel at all levels of specifications!

DOT • ATSM • NSF • FHA • FAA • CRD • TVA • FSS • CEPA



Detail all cracks, pores, & spalls.



Place RepTape over joints & cracks.



Cover tape onto deck surface with RepDeck Base Coat.



Spread RepDeck over surface for a Seamless Traffic System

TuffTex Materials
2209 Donley Drive
Austin, TX 78758
Office: (512) 617-7334



TuffTex Materials
RESTORATION MADE EASY



DETAILED INSTALLATION INSTRUCTIONS FOR EASE OF USE ARE AVAILABLE AND RECOMMENDED!

CAUTION:

READ SDS PRIOR TO USING PRODUCT

Use with adequate ventilation. Wear protective clothing, gloves and eye protection. (Goggles, Safety Glasses and/or Face Shield) Keep out of the reach of children. Do not take internally. In case of ingestion, seek medical help immediately. May cause skin irritation upon contact, especially if prolonged or repeated exposure. If skin contact occurs, wash immediately with soap and water and seek medical help as needed. If eye contact occurs, flush immediately, with clean water and seek medical help as needed. Dispose of waste material in accordance with federal, state and local requirements. Cured resins are Innocuous.

WARRANTY:

Due to the use of this product beyond our control, we assume no liability for damages of any kind, and the user accepts the product "as is" and without warranties, expressed or implied, from either TuffTex Materials or its agents. The suitability of the product for an intended use shall be solely up to the user. Our only obligation shall be to replace or pay for any material proved defective, with our liability limited to the purchase price of materials supplied by us.

DISCLAIMER:

Refer to the SDS sheet before use. The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of TuffTex Materials. Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Published technical data and instructions are subject to change without notice. Contact your local TuffTex distributor or technical representative for additional technical data and instructions.

OSHA Status:

This product is not considered to be a hazardous material under federal OSHA Hazard Communication Standard 29 CFR 1910.1200.

TuffTex Materials, Inc.

2209 Donley Drive

Austin, TX 78758

Office: (512) 617-7334