

RepTape MD

Highly Elastic, Multi-directional, Mesh Tape

DESCRIPTION:

RepTape MD is the newest and most innovative product on the market for completely masking expansion, contraction, cracking, control or other reflective joints and imperfections on any surfaces. **RepTape MD** is used in **TuffTex** decking systems. **RepTape MD** is a 4" (10 cm) wide, highly elastic, multi-directional, mesh tape for reinforcement of polyurethane, silicone, acrylic and cementitious coatings. **RepTape MD** features the most outstanding elongation and crack-bridging properties of any reinforcement tape in the industry. In normal applications of **TuffTex** polyurethane coatings, **RepTape MD** is capable of relieving and completely hiding failed sealant expansion and contraction of expansion joints and control joints in roofing, waterproofing, plywood, concrete and other areas where crack and joint bridging is required without the need to remove and replace the sealant before the **TuffTex** coating application. Please use the correct products that comply with VOC regulations as per federal, state, county and city regulations/codes at the place of installation of product.

USES:

- Concrete
- Cracks
- Flashings
- Other High Stress Areas
- Plywood
- Seams
- Joints

FEATURES:

- Excellent Reinforcement Of Stress Areas
- Exceptional Hiding Ability
- Bridges Cracks & Joints

COLOR:

Blue

PACKAGING:

Single Rolls – 4" x 280 feet (10.11 cm x 85.34 m). Sold individually or in cases of 4 rolls.

JOINTS, CRACKS, AND FLASHING:

Bridge the joints, cracks and flashing interface with plywood. Do not prime over **RepTape MD**. Apply 4" **RepTape MD** into prestriped 10 mils (254 microns) of basecoat while wet by gently embedding tape into coating or sealant. After 2 hours or more apply coat of basecoat and smooth onto adjacent surface.

PROTECTION:

The **RepTape MD** product must be protected from damage during the construction phase and must not be exposed to rain and condensation before coating.

TECHNICAL DATA

Average weight, observed	1.9 oz./sq. yd. (64.4 gm/sqm)
Thickness, observed	0.005" (0.127 mm)
Elongation (multi-directional)	300%
Elongation was measured in 360 Degree Direction	
Coverage per roll, length, observed	280 ft (80.34 meters)

SHELF LIFE AND STORAGE:

RepTape MD has a shelf life of 12 months from date of manufacture, when stored indoors at a temperature not greater than 75°(24°C) and not less than 50% relative humidity.

LIMITATIONS:

- Cannot withstand extended direct wear or abrasion without being embedded into sealant or coating.
- **RepTape MD** should be coated the same day as installed.
- Not for use over hot rubberized asphalt without written consent of **TuffTex Materials, Inc.**
- Surfaces must be dry, clean and free of foreign matter.

WARRANTY:

Due to the use of this product beyond our control, we assume no liability for damages of any kind, and the user accepts the product "as is" and without warranties, expressed or implied, from either **TuffTex Materials, Inc.** or its agents. The suitability of the product for an intended use shall be solely up to the user. Our only obligation shall be to replace or pay for any material proved defective, with our liability limited to the purchase price of materials supplied by us.

DISCLAIMER:

Refer to the SDS sheet before use. The information and recommendations set forth in this Product Data Sheet are based upon tests conducted by or on behalf of **TuffTex Materials, Inc.** Such information and recommendations set forth herein are subject to change and pertain to the product offered at the time of publication. Published technical data and instructions are subject to change without notice. Contact your local **TuffTex Materials, Inc.** distributor or technical representative for additional technical data and instructions.