

A single application coating that is LOW VOC Solution, Can Be Pigmented, Installed with brush/roller/spray equipment and can be a long-lasting solution (Tagged up to 10 Times) to graffiti tagging.

TuffTex RepShield is available in a variety of colors and clear finishes. Our Anti-graffiti can be applied directly to cover most existing graffiti and protect against future attacks.

REPSHIELD AG-Clear, Semi-Gloss Anti-graffiti, Tagged up to 4 Times
REPSHIELD XL-Clear, Semi-Gloss Anti-Graffiti, Tagged up to 12 times
REPSHIELD LV-Low VOC Anti-Graffiti, Tagged up to 4 Times

PRIMERLESS ADHESION*:

- | | |
|--|---|
| <input checked="" type="checkbox"/> Concrete | <input checked="" type="checkbox"/> Fiberglass |
| <input checked="" type="checkbox"/> Brick | <input checked="" type="checkbox"/> Metals |
| <input checked="" type="checkbox"/> Stone | <input checked="" type="checkbox"/> Pre-existing Coatings |

Coverage: Usage is typically 125 to 225 ft²/gal in one or two coats. Porous substrates, CMU (Concrete Masonry Units) may require more material.

Antigraffiti Removal: Most graffiti-tagging can easily be removed from protected surfaces using water under low pressure -1200psi (ASTM D7089 Clean-ability Level One).

Overview: TuffTex RepShield XL forms chemical bonds directly with the host surface to enhance adhesion properties without the need for abrasive blasting, priming, and extensive site preparation. Graffiti can be removed from coated areas using water under low pressure - 1200 psi (ASTM D7089 Clean-ability Level One).

Warranty: 5 Year Limited Warranty

Equipment:

- 1/2 Nap Roller, Brush or Graco GH933 spray Rig with a 7250 PSI at the spray Tip (5,19)
- Mix material for 5 minutes in 5 gall pails with a drill with an auger bit
- Spray product-at a distance of 10"-12" from substrate, 5"-6" on vertical and blow sprays.



Available in clear and a variety of colors.

It's REMARKABLE®.



PRIMARY BENEFITS & FEATURES:

- | | |
|---|--|
| <ul style="list-style-type: none">• Easy to clean with cold, low pressure water• Type II & III permanent (non-sacrificial) coating• One-part, one-coat application• Minimal surface preparation required | <ul style="list-style-type: none">• Long service life• Hydrophobic and waterproof• Breathable coating• Superior Flexibility |
|---|--|

**RESISTANT TO: WEATHERING | UV | WATER | TREME TEMPERATURES
CORROSION WIND-DRIVEN RAIN | FREEZE & THAW CYCLES | AGING**