

ARC

ALUMINUM RIGID CONDUIT



Codes & Standards Compliance:

- *UL 6A
- *ANSI C80.5
- *WW-C-540C Federal Specification
- *CSA C 22.2 No.45



www.rymcousa.com
1-833-RYMCO-US

RYMCO Aluminum Rigid Conduit (ARC) offers a lightweight, low-maintenance, corrosion-resistant alternative to steel conduit. It can be installed in various locations, including wet, dry, exposed, concealed, and hazardous areas according to NEC guidelines. Its composite construction ensures durability and corrosion resistance, suitable for indoor and outdoor use where traditional steel conduit may not be ideal.

Material:

Aluminum rigid conduit is made from 6063 aluminum alloy, specifically in T1 and T5 tempers.

Application:

RYMCO ARC is ideal for industrial facilities, commercial buildings, and outdoor installations needing durability against moisture, chemicals, and UV exposure. It's also suitable for residential construction to protect electrical wiring and transportation infrastructure due to its strength, lightweight design, and corrosion resistance, ensuring reliable performance and longevity in electrical conduit systems.

Looking for Steel Pipe?

Think of **RYMCO**. We **Con-du-it**.

ALUMINUM RIGID CONDUIT

Weights & Specifications (10' Lengths)

Nominal Size (IN)	OD (IN)	ID (IN)	Wall Thickness	Weight Per Piece
1/2	0.84	0.62	0.10	2.94
3/4	1.05	0.82	0.11	3.91
1	1.31	1.04	0.12	5.85
1-1/4	1.66	1.38	0.13	7.92
1-1/2	1.90	1.61	0.13	9.48
2	2.37	2.06	0.14	12.76
2-1/2	2.87	2.46	0.19	20.35
3	3.50	3.06	0.20	26.79
3-1/2	4.0	3.50	0.21	29.56
4	4.50	4.02	0.22	38.17

RYMCO USA makes no warranties expressed or implied including warranty of merchantability or fitness for a particular purpose. The specifications, descriptions, information and illustrated materials herein are submitted solely for evaluation by others and since the use of its information is not within its control, RYMCO USA assumes no obligation or liability for such information and does not guarantee result from the use of said products or the information herein. Reference should be made to the original or primary source data along with standard accepted industry practice. The material herein is as of the date of publication and is subject to change without notice. Please consult manufacturer for proper warehousing, storing, handling and installation



4715 Gasmer Dr, Houston, TX 77035
Toll Free: 1-833-RYMCO-US
www.rymcousa.com