



## NYLON SLINGS

- Used in conjunction with overhead cranes, hoists or winches
- Nylon slings are available in single or double ply to protect heavy, irregular sized loads from scratching or marring
- Slings must be checked frequently
- Should any surface area show signs of wear or cutting, the sling must be replaced immediately
- Each is tagged with manufacturer's name and capacity



### DOUBLE EYE SLING TYPE 3

- Commonly used as a basket and/or choker hitch
- For choker hitch pass one eye through the other flat eye, also makes for easy withdrawal from beneath loads



### TWISTED EYE SLING TYPE 4

- Reverse eyes make full functional contact with lifting hooks without the use of hardware
- Widely used for both choker and basket hitches



### ENDLESS SLING TYPE 5

- Most versatile and widely used sling
- The economical answer to most lifting problems
- Ideal for vertical, choker, and basket hitches

### LOAD LIMIT FOR TYPE 3-4 (LBS.)

Width"	Vertical		Choker		Basket	
	Single	Double	Single	Double	Single	Double
1	1600	3200	1280	2400	3200	6400
2	3100	6200	2480	4960	6200	12400
3	4700	8800	3760	7040	9400	17600
4	6200	11000	4960	8800	12400	22000

### LOAD LIMIT FOR TYPE 5 (LBS.)

Width"	Vertical		Choker		Basket	
	Single	Double	Single	Double	Single	Double
1	3200	6200	2560	4960	6400	12400
2	6200	12400	4960	9930	12400	24800
3	9400	17600	7520	14080	18800	35200
4	12400	22000	9920	17600	24800	44000

Type	Width"	Ply	3' Model No.	Price /Each	4' Model No.	Price /Each	6' Model No.	Price /Each	8' Model No.	Price /Each	10' Model No.	Price /Each	12' Model No.	Price /Each	
Type 3	1	Single	LU292		LU293		LU294		LU295		LU296		LU297		
		Double	LU316		LU317		LU318		LU319		LU320		LU321		
	2	Single	LU298		LU299		LU300		LU301		LU302		LU303		
		Double	LU322		LU323		LU324		LU325		LU326		LU327		
	3	Single	LU304		LU305		LU306		LU307		LU308		LU309		
		Double	LU328		LU329		LU330		LU331		LU332		LU333		
	4	Single	LU310		LU311		LU312		LU313		LU314		LU315		
		Double	LU334		LU335		LU336		LU337		LU338		LU339		
Type 4	1	Single	LU340		LU341		LU342		LU343		LU344		LU345		
		Double	LU364		LU365		LU366		LU367		LU368		LU369		
	2	Single	LU346		LU347		LU348		LU349		LU350		LU351		
		Double	LU370		LU371		LU372		LU373		LU374		LU375		
	3	Single	LU352		LU353		LU354		LU355		LU356		LU357		
		Double	LU376		LU377		LU378		LU379		LU380		LU381		
	4	Single	LU358		LU359		LU360		LU361		LU362		LU363		
		Double	LU382		LU383		LU384		LU385		LU386		LU387		
	Type 5	1	Single	LU388		LU389		LU390		LU391		LU392		LU393	
			Double	LU412		LU413		LU414		LU415		LU416		LU417	
		2	Single	LU394		LU395		LU396		LU397		LU398		LU399	
			Double	LU418		LU419		LU420		LU421		LU422		LU423	
3		Single	LU400		LU401		LU402		LU403		LU404		LU405		
		Double	LU424		LU425		LU426		LU427		LU428		LU429		
4		Single	LU406		LU407		LU408		LU409		LU410		LU411		
		Double	LU430		LU431		LU432		LU433		LU434		LU435		

Note: Other sizes, capacities and options available

## POLYESTER ROUND SLINGS

- Constructed from multiple high tenacity polyester yarns in an endless/continuous loop
- Excellent resistance to ultra-violet light, rotting and mildew
- The high flexibility allows the sling to conform to the load for a secure hold
- No loss of strength when used in water
- Lightweight, easy to rig, store and clean
- Hook and load contact points can be rotated to extend the service life
- Seamless cover, no edges to wear out
- Maximum temperature exposure: 194°F



Model No.	Width'	Length'	Colour	Capacity lbs.			Price /Each
				Vertical	Choker	90° Basket	
LT569	2	4	Purple	3000	2400	6000	
LT570	2	6	Purple	3000	2400	6000	
LT571	2	8	Purple	3000	2400	6000	
LT572	2	4	Green	6000	4800	12000	
LT573	2	6	Green	6000	4800	12000	
LT574	2	8	Green	6000	4800	12000	
LT575	2	6	Yellow	9000	7200	18000	
LT576	2	8	Yellow	9000	7200	18000	

Model No.	Width'	Length'	Colour	Capacity lbs.			Price /Each
				Vertical	Choker	90° Basket	
LT577	2	10	Yellow	9000	7200	18000	
LT578	3	6	Red	14000	11200	28000	
LT579	3	8	Red	14000	11200	28000	
LT580	3	10	Red	14000	11200	28000	
LT581	4	8	Blue	23000	18400	46000	
LT582	4	10	Blue	23000	18400	46000	
LT583	4	12	Blue	23000	18400	46000	

Note: Other lengths available upon request