

CASTERS & WHEELS

PROTECH™ POLYOLEFIN WHEELS

- Non-marking ALTech treaded wheel is securely fastened to its polyolefin core
- Highly resistant to most chemicals and excellent for all floor surfaces
- Provides for high load capacities and is rust-proof
- Quiet and easy rolling
- Shock absorbing and rejects floor debris
- Prolongs equipment life
- Temperature: -43°C to 82°C
- Durometer: 55 - 65 A Scale

Excellent for:

- Platform trucks
- Food service equipment
- Hotel equipment
- Small waste bins
- Abusive applications
- Large stock trucks
- Factory use
- Textile carts



Diameter"	Tread Width"	Bearing Type	Cap. lbs.	Hub Length"	Bearing Bore"	Model No.	Price /Each
4	1 1/2	Roller	325	1 3/16	1/2	MN784	
5	1 1/2	Roller	350	1 3/16	1/2	MN785	
6	1 1/2	Roller	375	1 3/16	1/2	MN786	
4	2	Roller	300	2 3/8	1/2	MG524	
5	2	Roller	375	2 3/8	1/2	MG525	
6	2	Roller	450	2 3/8	1/2	MG526	
8	2	Roller	600	2 3/8	1/2	MG527	
10	2.5	Roller	1000	2 27/32	3/4	MN787	

P.O.A

ENVIROTHANE™ WHEELS

- Solid non-marking polyurethane used for high load capacities
- Harder than soft rubber and softer than hard rubber
- Top quality wheel that will not damage your floors and will not develop flat spots under standing loads
- Government approved
- Temperature: -43°C to 110°C
- Durometer: 45 - 65 D Scale

Excellent for:

- Platform trucks
- Food service equipment
- Hotel equipment
- Small waste bins
- Large stock trucks
- Factory use
- Textile carts
- Abusive applications



Diameter"	Tread Width"	Bearing Type	Cap. lbs.	Hub Length"	Bearing Bore"	Model No.	Price /Each
2	7/8	Nylon/Steel	100	1	1/4	MG532	
2 1/2	7/8	Nylon/Steel	100	1	1/4	MG533	
3	7/8	Nylon/Steel	100	1	5/16	MG534	
3	1	Nylon	150	1 3/8	5/16	MG535	
3	1 1/4	Nylon	250	1 5/8	5/16	MG536	
4	1	Nylon	150	1 3/8	5/16	MG537	
4	1 1/4	Nylon	250	1 5/8	5/16	MG538	
4	1 1/2	Plain	500	1 3/4	3/8	MG539	
4	2	Roller	650	2 3/16	1/2	MG540	
5	1	Nylon	175	1 3/8	5/16	MG541	
5	1 1/4	Nylon	350	1 5/8	5/16	MG542	
5	1 1/2	Roller	600	1 3/4	3/8	MG543	
5	2	Roller	1200	2 3/16	1/2	MG544	
6	1 1/2	Roller	600	1 3/4	1/2	MG545	
6	2	Roller	1300	2 3/16	1/2	MG546	
6	2 1/2	Roller	1500	2 3/4	3/4	MG547	

PHENOLIC WHEELS

- Made of macerated canvas impregnated with phenolic resin
- Resistant to grease, oil and most chemical substances
- Non-marking and provides for high floor protection
- Lightweight, and even maintains a high load rating
- Temperature: -43°C to 82°C
- Durometer: 120 Rockwell E

Excellent for:

- Factory use
- Heavy material handling
- Waste bins
- Platform trucks
- Stock trucks
- Heavy loads
- Bakery applications



Diameter"	Tread Width"	Bearing Type	Cap. lbs.	Hub Length"	Bearing Bore"	Model No.	Price /Each
3	1 1/4	Steel	400	1 3/8	5/16	MG583	
4	1 1/4	Steel	400	1 3/8	5/16	MG584	
4	1 1/2	Plain	600	1 3/4	1 3/16	MG587	
4	1 1/2	Roller	600	1 3/4	1/2	MG588	
4	2	Plain	800	2 3/16	1 3/16	MG589	
4	2	Roller	800	2 3/16	1/2	MG590	
5	1 1/4	Steel	400	1 3/8	5/16	MG591	
5	1 1/2	Roller	600	1 3/4	1/2	MG593	
5	2	Plain	1000	2 3/16	1 3/16	MG594	
5	2	Roller	1000	2 3/16	1/2	MG595	
6	1 1/2	Plain	800	1 5/8	1 3/16	MN778	
6	1 1/2	Roller	800	1 13/16	1/2	MN779	
6	2	Plain	1200	2 3/16	1 3/16	MN780	
6	2	Roller	1200	2 3/8	1/2	MN781	
8	2	Plain	1400	2 3/16	1 3/16	MN782	
8	2	Roller	1400	2 3/8	1/2	MN783	

ALTHANE™ WHEELS

- Lightweight
- Economical and high in impact strength
- Non-marking, non-chipping, oil and chemical resistant and non-absorbent
- Steam cleanable wheel provides for floor protection
- Temperature: -43°C to 82°C
- Durometer: 65 - 70 D Scale

Excellent for:

- Platform trucks
- Food service equipment
- Hotel equipment
- Small waste bins
- Abusive applications
- Large stock trucks
- Factory use
- Textile carts



Diameter"	Tread Width"	Bearing Type	Cap. lbs.	Hub Length"	Bearing Bore"	Model No.	Price /Each
4	2	Roller	750	2 3/16	1/2	MG528	
5	2	Roller	1000	2 3/16	1/2	MG529	
6	2	Roller	1150	2 3/16	1/2	MG530	
8	2	Roller	1300	2 3/16	1/2	MG531	

MOLD-ON RUBBER WHEELS

- Mold-on rubber is secured to semi-steel core for full floor protection and quiet movement
- High degree of resistance to shock or vibration
- Highly economical rubber tire
- Prolongs equipment life
- Temperature: -43°C to 82°C
- Durometer: 70 - 75 A Scale

Excellent for:

- Platform trucks
- Food service equipment
- Hotel equipment
- Small waste bins
- Abusive applications
- Large stock trucks
- Factory use
- Textile carts



Diameter"	Tread Width"	Bearing Type	Cap. lbs.	Hub Length"	Bearing Bore"	Model No.	Price /Each
4	1 1/2	Roller	280	1 3/4	1/2	MG553	
4	2	Roller	370	2 3/16	1/2	MG554	
5	1 1/2	Roller	350	1 3/4	1/2	MG555	
5	2	Roller	470	2 3/16	1/2	MG556	
6	2	Roller	400	1 3/4	3/4	MH296	
6	1 1/2	Roller	420	1 3/4	1/2	MG557	
6	2	Roller	560	2 3/16	1/2	MG558	
6	2 1/2	Roller	620	2 3/4	3/4	MG559	
6	3	Roller	730	3 1/4	3/4	MG560	
6	3	Tapered	750	3 1/2	1	MG561	
8	2	Roller	595	2 3/4	3/4	MH297	
8	2 1/2	Plain	800	2 3/4	1 15/16	MG563	
8	2 1/2	Roller	830	2 3/4	3/4	MG562	
8	3	Roller	900	3 1/4	3/4	MG564	
8	3	Tempered	900	3 1/4	1 3/4	MG565	
10	2	Roller	950	2 1/4	3/4	MN694	
12	2 1/2	Roller	950	2 27/32	1	MN693	

POLYOLEFIN WHEELS

- Lightweight, very economical and high in impact strength
- Non-marking, non-chipping, oil and chemical resistant and non-absorbent
- Steam cleanable wheel provides for floor protection
- Easy to maintain
- Temperature: -43°C to 82°C
- Durometer: 65 - 70 D Scale


Excellent for:

- Platform trucks
- Factory use



Diameter"	Tread Width"	Bearing Type	Cap. lbs.	Hub Length"	Bearing Bore"	Model No.	Price /Each
2	7/8	Plain	75	1	1/4	MG610	
3	1 1/4	Plain	270	19/16	1 3/16	MC064	
4	1	Plain	150	1 3/8	5/16	MG612	
4	1 1/2	Plain	400	1 3/4	1 3/16	MG613	
4	2	Roller	450	2 3/16	1/2	MG614	
5	1 1/2	Roller	450	1 3/4	1/2	MG615	
5	2	Roller	650	2 3/16	1/2	MG616	
6	1 1/2	Roller	550	1 3/4	1/2	MG617	
6	2	Roller	750	2 3/16	1/2	MG618	

WHEELS



Diameter"	Tread Width"	Bearing Type	Cap. lbs.	Bearing Bore"	Wheel Type	Model No.	Price /Each
A.	5	2	Roller	1500	3/4	Cast Iron	MC298
B.	8	2	Roller	1000	3/4	Phenolic	MC337
B.	12	2 1/2	Roller	3000	1	Phenolic	MC340
C.	10	3	Ball	350	3/4	Pneumatic	ML069
D.	5	1 1/4	Plain	250	5/16	Hard Rubber	MG552